TRIPACT LED P 3750LM PMMA II KL. IP40/ IP20 595X595 830 (42W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	658020
Ingress protection:	IP40/20
Nominal power [W]:	42
Luminous flux [lm]*:	3750
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	F
Material of the body:	ABS
Diffuser material:	PMMA
Diffuser type:	OPAL

CHARACTERISTICS

TRIPACT LED is a combination of proven LED solutions with remarkable DESIGN. Luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED GO! panels and an evenly highlighted opal diffuser. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus.

TRIPACT LED P 3750LM PMMA II KL. IP40/ IP20 595X595 830 (42W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	658020
Light source:	LED module
Nominal power [W]:	42
Rated power of the luminaire [W]:	43
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	3750
Luminous efficacy [lm/W]:	87
Energy efficiency class:	F
Electrical protection class:	II
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.95
LED lifespan L70B50 [h]:	132000
Diffuser material:	PMMA
Diffuser type:	OPAL
Diffuser colour:	white
Material of the body:	ABS
Colour of the body:	white


Dimensions (H/W/T/S) [mm]:	595/595/93
Mounting dimensions [mm]:	595/595
Ingress protection:	IP40/20
Mounting version:	recessed
Working temperature [°C]:	from -25 to +35
Net weight [kg]:	1.800
EAN:	5905963658020
Category type:	troffers
AC voltage range [V]:	198 - 264
DC voltage range [V]:	176 - 276
LED lifespan L80B10 [h]:	84000
LED lifespan L90B10 [h]:	42000
Light distribution type:	lambertian
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	5
Warranty [years]:	5
Manual:	Download PDF
CE certificate:	251/2023
Plik LDT:	Download

TRIPACT LED P 3750LM PMMA II KL. IP40/ IP20 595X595 830 (42W)


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
658372	Diffuser TRIPACT
374845	Frame adapter KG 635x635 WHITE



Diffuser TRIPACT (658372)



Frame adapter KG 635x635 WHITE (374845)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 251/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl