


TRIPACT LED P 4050LM PMMA DALI I KL. IP40/ IP20

595X595 840 (42W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	658198
Ingress protection:	IP40/20
Nominal power [W]:	42
Luminous flux [lm]*:	4050
Colour rendering index:	80
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Diffuser material:	PMMA
Diffuser type:	OPAL

CHARACTERISTICS

TRIPACT LED is a combination of proven LED solutions with remarkable DESIGN. Luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED GO! panels and an evenly highlighted opal diffuser. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus.

TRIPACT LED P 4050LM PMMA DALI I KL. IP40/ IP20

595X595 840 (42W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	658198	Dimensions (H/W/T/S) [mm]:	595/595/93
Light source:	LED module	Mounting dimensions [mm]:	595/595
Nominal power [W]:	42	Ingress protection:	IP40/20
Rated power of the luminaire [W]:	43	Mounting version:	recessed
Supply voltage [V]:	220-240	Working temperature [°C]:	from -25 to +35
Frequency [Hz]:	50 - 60	DIMM DALI:	yes
Luminous flux [lm]:	4050	Net weight [kg]:	1.900
Luminous efficacy [lm/W]:	94	EAN:	5905963658198
Energy efficiency class:	E	Category type:	troffers
Electrical protection class:	I	AC voltage range [V]:	198 - 264
Colour temperature [K]:	4000	DC voltage range [V]:	176 - 276
Colour rendering index:	80	LED lifespan L80B20 [h]:	84000
SDCM:	≤ 3	LED lifespan L90B10 [h]:	42000
Power factor:	0.95	Light distribution type:	lambertian
LED lifespan L70B50 [h]:	132000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	PMMA	Warranty [years]:	5
Diffuser type:	OPAL	Warranty [years]:	5
Diffuser colour:	white	Manual:	Download PDF
Material of the body:	ABS	CE certificate:	251/2023
Colour of the body:	white	Plik LDT:	Download


TRIPACT LED P 4050LM PMMA DALI I KL. IP40/ IP20

595X595 840 (42W)


DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
658372	Diffuser TRIPACT
999543	Plasterboard recessing kit 630x630 white (steel version)



Diffuser TRIPACT (658372)




Plasterboard recessing kit 630x630 white (steel version) (999543)

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 251/2023