

LINERO LED PRO 1204MM 36350LM 840 IP66 DALI CN 269W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	115813
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	269
Luminous flux [lm]*:	36350
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
Electrical protection class:	I
Energy efficiency class:	D
Material of the body:	aluminium

CHARACTERISTICS

A range of lightweight, hermetically sealed High-Bay linear luminaires, made from extruded aluminium, featuring a heat sink to dissipate excess heat and a separate compartment for the power supply (also made from extruded aluminium). It combines the benefits of durability and airtightness with the highest luminous efficacy in Class A – up to 195 lm/W. The uncompromising, modern design represents a breakthrough in the design of efficient yet economical industrial luminaires. The modular construction allows for maximum luminous flux at a low cost and compact size. Professional optics made from durable polycarbonate (PC) offer great flexibility in selecting the optimal solution, even at significant installation heights.

APPLICATION

Designed with the most demanding production and warehouse spaces in mind, where the highest quality and quantity of light at the lowest possible investment cost are the priority. The option of wall mounting or mounting using an articulated arm is an additional installation feature.

LINERO LED PRO 1204MM 36350LM 840 IP66 DALI CN 269W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	115813	Material of the body:	aluminium
EAN:	5905963115813	Colour of the body:	RAL9005
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	1204/64/205
Rated power of the luminaire [W]:	269	Mounting dimensions [mm]:	265
Luminous flux [lm]:	36350	Impact resistance:	IK09
Supply voltage [V]:	220-240	Ingress protection:	IP66
AC voltage range [V]:	176-264	Mounting version:	surface, suspended
DC voltage range [V]:	176-264	Working temperature [°C]:	from -40 to +35
Frequency [Hz]:	0/50-60	Tilt angle adjustment [°]:	yes
Luminous efficacy [lm/W]:	135	DIMM DALI:	yes
Energy efficiency class:	D	Dimensions of single box [mm]:	1207/65/205
Electrical protection class:	I	Number on the palette [pcs]:	90
Colour temperature [K]:	4000	Net weight [kg]:	3.270
Color rendering index (Ra) >:	80	Light distribution type:	CW
LED lifespan L70B50 [h]:	53000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L80B10 [h]:	108000	Warranty [years]:	5
LED lifespan L90B10 [h]:	159000	CE certificate:	121/2026
Surge protection [kV]:	1	Manual:	Download PDF
Diffuser material:	PC	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Diffuser type:	matrix led	Plik LDT:	Download
Optics material:	PC		

Card creation date: 22 July 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 121/2026



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl