

# ASCENT TWIN LED RGBW H DMX I CL. IP66 35D 55W

DETAILED CARD



## TECHNICAL PARAMETERS

|                                    |        |
|------------------------------------|--------|
| Index:                             | 114984 |
| Ingress protection:                | IP66   |
| Impact resistance:                 | IK08   |
| Rated power of the luminaire [W]*: | 55     |
| Luminous flux [lm]*:               | 3329   |
| Colour temperature [K]:            | 5500   |
| Color rendering index (Ra) >:      | 52.7   |
| SDCM:                              | 6      |
| Electrical protection class:       | I      |
| Energy efficiency class:           | G      |

## CHARACTERISTICS

The Ascent Twin LED RGBW are high-performance floodlights designed for professional lighting applications. They are characterised by their robust construction and precision craftsmanship. The body, made from deep black aluminium (RAL9005), ensures high durability and resistance to adverse weather conditions. A transparent glass diffuser protects the two-section module of high-performance LEDs, whilst a wide selection of optics allows the light beam to be perfectly tailored to the project's requirements.

RGBW technology, supported by DMX control, enables a full colour palette including white light (5500 K), guaranteeing high-quality lighting, precise colour rendering and seamless control over lighting effects. A variety of beam angles – both symmetrical (15°, 25°, 35°, 60°) and rectangular (20x40°) – allow the character of the light output to be tailored to the specific requirements of the venue: from wide, even illumination to narrow, focused lighting accents.

High mechanical resistance (IK08) and an IP66-rated enclosure ensure reliable and trouble-free operation in demanding environmental conditions (within a temperature range of -20°C to +35°C). Surface-mounted installation with an adjustable bracket and the availability of two mounting variants (H and L versions) ensure configuration flexibility and easy adaptation of the luminaire to various design requirements.

## APPLICATION

Ascent Twin LED RGBW floodlights are widely used in landscape, architectural, urban and decorative lighting. They are ideal for illuminating building façades, architectural details, monuments and engineering structures, as well as green spaces, parks and prestigious public spaces.

Thanks to precise colour control and a wide range of available optics (including a 20x40° rectangular optic), they enable the creation of striking lighting compositions, dynamic colour scenes and atmospheric illuminations that emphasise the character and aesthetics of the surroundings.

The luminaires are equipped with DMX control as standard, allowing for full control over lighting parameters, synchronisation with other devices and the creation of advanced, programmable lighting effects.

This is a professional solution designed for projects where light is a key element in spatial design and atmosphere creation.

# ASCENT TWIN LED RGBW H DMX I CL. IP66 35D 55W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |               |                            |                                                                             |
|-----------------------------------|---------------|----------------------------|-----------------------------------------------------------------------------|
| Index:                            | 114984        | Dimensions (H/W/T/S) [mm]: | 300/200/170                                                                 |
| EAN:                              | 5905963114984 | Mounting dimensions [mm]:  | 160                                                                         |
| Light source:                     | LED module    | Impact resistance:         | IK08                                                                        |
| Rated power of the luminaire [W]: | 55            | Ingress protection:        | IP66                                                                        |
| Supply voltage [V]:               | 220-240       | Mounting version:          | surface                                                                     |
| Frequency [Hz]:                   | 50            | Working temperature [°C]:  | from -20 to +35                                                             |
| Luminous flux [lm]:               | 3329          | Net weight [kg]:           | 4                                                                           |
| Luminous efficacy [lm/W]:         | 61            | Category type:             | floodlights                                                                 |
| Energy efficiency class:          | G             | Version:                   | H                                                                           |
| Electrical protection class:      | I             | LED lifespan L70B50 [h]:   | 80000                                                                       |
| Colour temperature [K]:           | 5500          | LED lifespan L80B10 [h]:   | 50000                                                                       |
| Color rendering index (Ra) >:     | 52.7          | LED lifespan L90B10 [h]:   | 24000                                                                       |
| SDCM:                             | 6             | Light distribution type:   | symmetric                                                                   |
| Beam angle [°]:                   | 35            | Photobiological safety:    | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Surge protection [kV]:            | 4             | Warranty [years]:          | 5                                                                           |
| Diffuser material:                | glass         | CE certificate:            | <a href="#">122/2026</a>                                                    |
| Diffuser type:                    | transparent   | Manual:                    | <a href="#">Download PDF</a>                                                |
| Material of the body:             | aluminium     | Plik LDT:                  | <a href="#">Download</a>                                                    |
| Colour of the body:               | RAL9005       |                            |                                                                             |