

BARIS 52 LED Z 1143MM 7900LM 840 IP44 I CL. DALI EM3H PLX ANODA CO 51W SINGLE (GKO)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44
Impact resistance:	IK06
Rated power of the luminaire [W]*:	51
Luminous flux [lm]*:	7900
Colour temperature [K]:	4000
Colour of the body:	C0 anode
Diffuser material:	PC
Diffuser type:	OPAL
Mounting version:	suspended

CHARACTERISTICS

Suspended or surface-mounted luminaire with classic proportions and modern design. The housing of the luminaire is made of an anodized aluminum profile in gray or an aluminum profile painted in white or black (other colors available on request). The optical system is in the form of a prismatic diffuser (PRM); a dedicated, flexible opal diffuser evenly illuminating the luminaire or with a louver that meets the stringent glare requirements UGR <19 covered with a transparent cover. The modularity and dismantling of the luminaire allow for the replacement of electronic components, such as the LED strip, power supply, and replacement of the lampshade by qualified persons. The luminaire profile has been adapted to work with intelligent IoT modules, which will additionally optimize the level and amount of light provided by it, as well as the direct/indirect version that allows some of the light to be directed upwards, illuminating the ceiling. The luminaire is equipped with a unique suspension system that facilitates the installation of the luminaire and adjustment of the suspension. All Baris 52 LED Single suspended luminaires include 1.2m long pendants with a socket in the set and are equipped with a diffuser.

APPLICATION

The luminaire is intended for indoor use. It is used as the main light source and favors office work that requires concentrated vision. The unique design, the energy-saving LED modules, and the ability to work with external lighting control systems in the DALI standard predestine the luminaire for use in modern office buildings of class A+, with a particular focus on offices, prestigious rooms, conference rooms, passageways, and wherever IP44 protection is required. Baris 52 LED Single is, as the name suggests, a single lighting element with a specific length. To create a line of length up to 6 meters without connecting the profile and up to 25 meters without connecting the lampshade, version BARIS 52 LED.

BARIS 52 LED Z 1143MM 7900LM 840 IP44 I CL. DALI EM3H PLX ANODA CO 51W SINGLE (GKO)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	164736	Ingress protection:	IP44
Light source:	LED module	Mounting version:	suspended
Rated power of the luminaire [W]:	51	Working temperature [°C]:	from 0 to +35
Luminous flux [lm]:	7900	DIMM DALI:	yes
Supply voltage [V]:	220 - 240	Net weight [kg]:	2.100
Frequency [Hz]:	50 - 60	Emergency lighting [h]:	3
Luminous efficacy [lm/W]:	155	Category of application:	office lighting
Energy efficiency class:	D	Battery:	Li-Ion
Electrical protection class:	I	Battery capacity [mAh]:	5000
Colour temperature [K]:	4000	Autotest:	yes
Color rendering index (Ra) >:	80	Operating mode:	emergency-network
SDCM:	3	Emergency luminous flux [lm]*:	350
LED lifespan L70B50 [h]:	150000	Warranty [years]:	5
LED lifespan L80B10 [h]:	100000	CE certificate:	32/2026
LED lifespan L90B10 [h]:	50000	ENEC Certificate:	
Diffuser material:	PC	PZH certificate:	B-BK-60112-0357/2023
Diffuser type:	OPAL	Environmental Product Declaration (EPD):	852/2025
Colour of the body:	CO anode	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	1143/69/52	ISO Certificates:	9001:2015, 14001:2015, 45001:2018, 50001:2018
Impact resistance:	IK06		

LIGHT CURVES



BARIS 52 LED Z 1143MM 7900LM 840 IP44 I CL. DALI EM3H PLX ANODA CO 51W SINGLE (GKO)

DETAILED CARD
TECHNICAL PICTURES



Card creation date:10 September 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric andelectronic waste equipment regulations (WEEE).



Certificate CE - Nr: 32/2026



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl