

SOLPACT LED P 2300LM PMMA II KL. IP40/20 595X595MM 830 (24W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|---------|
| Index: | 658389 |
| Ingress protection: | IP40/20 |
| Nominal power [W]: | 24 |
| Luminous flux [lm]*: | 2300 |
| Color rendering index (Ra) >: | 80 |
| SDCM: | 3 |
| Energy efficiency class: | F |
| Material of the body: | ABS |
| Diffuser material: | PMMA |
| Diffuser type: | OPAL |

CHARACTERISTICS

SOLPACT LED is a combination of proven LED solutions with remarkable DESIGN. Luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED GO! panels and an evenly highlighted opal diffuser. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus.

SOLPACT LED P 2300LM PMMA II KL. IP40/20 595X595MM 830 (24W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE


| | | | |
|--|------------|----------------------------------|---|
| Index: | 658389 | Mounting dimensions [mm]: | 595/595 |
| Light source: | LED module | Ingress protection: | IP40/20 |
| Nominal power [W]: | 24 | Mounting version: | recessed |
| Rated power of the luminaire [W]: | 25 | Working temperature [°C]: | from -25 to +35 |
| Supply voltage [V]: | 220-240 | Net weight [kg]: | 1.800 |
| Frequency [Hz]: | 50 - 60 | Warranty [years]: | 5 |
| Luminous flux [lm]: | 2300 | EAN: | 5905963658389 |
| Energy efficiency class: | F | Category type: | troffers |
| Electrical protection class: | II | AC voltage range [V]: | 198 - 264 |
| Colour temperature [K]: | 3000 | DC voltage range [V]: | 176 - 276 |
| Color rendering index (Ra) >: | 80 | UGR (4H8H): | 17-23 |
| SDCM: | 3 | LED lifespan L80B10 [h]: | 84000 |
| Power factor: | 0.95 | LED lifespan L90B10 [h]: | 42000 |
| LED lifespan L70B50 [h]: | 132000 | Light distribution type: | lambertian |
| Diffuser material: | PMMA | CE certificate: | 252/2023 |
| Diffuser type: | OPAL | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Diffuser colour: | white | Luminous efficacy [lm/W]: | 92 |
| Material of the body: | ABS | Warranty [years]: | 5 |
| Colour of the body: | white | Manual: | Download PDF |
| Dimensions (H/W/T/S) [mm]: | 595/595/87 | Plik LDT: | Download |

SOLPACT LED P 2300LM PMMA II KL. IP40/20 595X595MM 830 (24W)

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|--|
| 999543 | Plasterboard recessing kit 630x630 white (steel version) |



Plasterboard recessing kit 630x630
white (steel version) (999543)

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 252/2023