## CORPACT LED P 2300LM PMMA DALI I KL. IP40/20 595X595MM 830 (24W)

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

Index:	658655
Ingress protection:	IP40/20
Nominal power [W]:	24
Luminous flux [lm]*:	2300
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	F
Material of the body:	ABS
Diffuser material:	PMMA
Diffuser type:	OPAL

### **CHARACTERISTICS**

CORPACT LED is a combination of proven LED solutions with remarkable DESIGN. Luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED GO! panels and an evenly highlighted opal diffuser. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

### **APPLICATION**

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus.



# CORPACT LED P 2300LM PMMA DALI I KL. IP40/20 595X595MM 830 (24W)

**DETAILED CARD** 

### **TECHNICAL PARAMETERS TABLE**

Index:	658655
Light source:	LED module
Nominal power [W]:	24
Rated power of the luminaire [W]:	25
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	2300
Energy efficiency class:	F
Electrical protection class:	1
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.95
LED lifespan L70B50 [h]:	132000
Diffuser material:	PMMA
Diffuser type:	OPAL
Diffuser colour:	white
Material of the body:	ABS
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	595/595/93

Mounting dimensions [mm]:	595/595
Ingress protection:	IP40/20
Mounting version:	recessed
Working temperature [°C]:	from -25 to +35
DIMM 1-10V:	yes
DIMM DALI:	yes
Net weight [kg]:	1.900
Warranty [years]:	5
EAN:	5905963658655
Category type:	troffers
AC voltage range [V]:	198 - 264
DC voltage range [V]:	176 - 276
UGR (4H8H):	17-23
Light distribution type:	lambertian
CE certificate:	250/2023
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Luminous efficacy [lm/W]:	92
Manual:	Download PDF
Plik LDT:	Download




# CORPACT LED P 2300LM PMMA DALI I KL. IP40/20 595X595MM 830 (24W)

**DETAILED CARD** 

### **ACCESSORIES AVAILABLE**

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)



Plasterboard recessing kit 630x630 white (steel version) (999543)

Card creation date: 03 January 2025



