

CORPACT LED P 2300LM PMMA II KL. IP40/20 595X595MM 830 (24W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|---------|
| Index: | 658594 |
| Ingress protection: | IP40/20 |
| Nominal power [W]: | 24 |
| Luminous flux [lm]*: | 2300 |
| Colour rendering index: | >80 |
| SDCM: | ≤ 3 |
| Energy efficiency class: | F |
| Material of the body: | ABS |
| Diffuser material: | PMMA |
| Diffuser type: | OPAL |

CHARACTERISTICS

CORPACT LED is a combination of proven LED solutions with remarkable DESIGN. Luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED GO! panels and an evenly highlighted opal diffuser. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus.

CORPACT LED P 2300LM PMMA II KL. IP40/20 595X595MM 830 (24W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|------------|-----------------------------------|---|
| Nominal power [W]: | 24 | Colour of the body: | white |
| Index: | 658594 | Dimensions (H/W/T/S) [mm]: | 595/595/93 |
| Colour temperature [K]: | 3000 | Mounting dimensions [mm]: | 595/595 |
| Light source: | LED module | Ingress protection: | IP40/20 |
| Luminous flux [lm]: | 2300 | Mounting version: | recessed |
| Diffuser type: | OPAL | Working temperature [°C]: | from -25 to +35 |
| Rated power of the luminaire [W]: | 25 | Net weight [kg]: | 1.800 |
| Supply voltage [V]: | 220-240 | Warranty [years]: | 5 |
| Energy efficiency class: | F | EAN: | 5905963658594 |
| Frequency [Hz]: | 50 - 60 | Category type: | louvres |
| Electrical protection class: | II | AC voltage range [V]: | 198 - 264 |
| Colour rendering index: | >80 | DC voltage range [V]: | 176 - 276 |
| SDCM: | ≤ 3 | UGR (4H8H): | 17-23 |
| Power factor: | 0.95 | Light distribution type: | lambertian |
| LED lifespan L70B50 [h]: | 132000 | CE certificate: | 250/2023 |
| Diffuser material: | PMMA | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Diffuser colour: | white | Luminous efficacy [lm/W]: | 92 |
| Material of the body: | ABS | Manual: | Download PDF |
| | | Pliik LDT: | Download |

CORPACT LED P 2300LM PMMA II KL. IP40/20 595X595MM 830 (24W)

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|--|
| 999543 | Plasterboard recessing kit 630x630 white (steel version) |



Plasterboard recessing kit 630x630
white (steel version) (999543)

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 250/2023