

CORPACT LED P 2300LM PMMA II KL. IP40/20 595X595MM 830 (24W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	658594
Ingress protection:	IP40/20
Nominal power [W]:	24
Luminous flux [lm]*:	2300
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	F
Material of the body:	ABS
Diffuser material:	PMMA
Diffuser type:	OPAL

CHARACTERISTICS

CORPACT LED is a combination of proven LED solutions with remarkable DESIGN. Luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED GO! panels and an evenly highlighted opal diffuser. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus.

CORPACT LED P 2300LM PMMA II KL. IP40/20 595X595MM 830 (24W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	658594	Dimensions (H/W/T/S) [mm]:	595/595/93
Light source:	LED module	Mounting dimensions [mm]:	595/595
Nominal power [W]:	24	Ingress protection:	IP40/20
Rated power of the luminaire [W]:	25	Mounting version:	recessed
Supply voltage [V]:	220-240	Working temperature [°C]:	from -25 to +35
Frequency [Hz]:	50 - 60	Net weight [kg]:	1.800
Luminous flux [lm]:	2300	Warranty [years]:	5
Energy efficiency class:	F	EAN:	5905963658594
Electrical protection class:	II	Category type:	troffers
Colour temperature [K]:	3000	AC voltage range [V]:	198 - 264
Color rendering index (Ra) >:	80	DC voltage range [V]:	176 - 276
SDCM:	3	UGR (4H8H):	17-23
Power factor:	0.95	Light distribution type:	lambertian
LED lifespan L70B50 [h]:	132000	CE certificate:	250/2023
Diffuser material:	PMMA	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser type:	OPAL	Luminous efficacy [lm/W]:	92
Diffuser colour:	white	Manual:	Download PDF
Material of the body:	ABS	Plik LDT:	Download
Colour of the body:	white		

CORPACT LED P 2300LM PMMA II KL. IP40/20 595X595MM 830 (24W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
374845	Frame adapter KG 635x635 WHITE



Frame adapter KG 635x635
WHITE (374845)

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 250/2023