CORPACT LED P 5300LM PMMA DALI I KL. IP40/20 595X595MM 830 (60W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	658693
Ingress protection:	IP40/20
Nominal power [W]:	60
Luminous flux [lm]*:	5300
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	F
Material of the body:	ABS
Diffuser material:	PMMA
Diffuser type:	OPAL

CHARACTERISTICS

CORPACT LED is a combination of proven LED solutions with remarkable DESIGN. Luminaire designed for installation in modular ceilings or surface mounting. Equipped with energy-saving LED GO! panels and an evenly highlighted opal diffuser. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus.

CORPACT LED P 5300LM PMMA DALI I KL. IP40/20 595X595MM 830 (60W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	658693
Light source:	LED module
Nominal power [W]:	60
Rated power of the luminaire [W]:	65
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	5300
Energy efficiency class:	F
Electrical protection class:	I
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.95
LED lifespan L70B50 [h]:	132000
Diffuser material:	PMMA
Diffuser type:	OPAL
Diffuser colour:	white
Material of the body:	ABS
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	595/595/93


Mounting dimensions [mm]:	595/595
Ingress protection:	IP40/20
Mounting version:	recessed
Working temperature [°C]:	from -25 to +35
DIMM 1-10V:	yes
DIMM DALI:	yes
Net weight [kg]:	1.900
Warranty [years]:	5
EAN:	5905963658693
Category type:	troffers
AC voltage range [V]:	198 - 264
DC voltage range [V]:	176 - 276
UGR (4H8H):	17-23
Light distribution type:	lambertian
CE certificate:	250/2023
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Luminous efficacy [lm/W]:	81
Manual:	Download PDF
Plik LDT:	Download

CORPACT LED P 5300LM PMMA DALI I KL. IP40/20 595X595MM 830 (60W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
374845	Frame adapter KG 635x635 WHITE



Frame adapter KG 635x635
WHITE (374845)

Card creation date: 03 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 250/2023

LENA LIGHTING
Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl