

MADERA ALTUS LED EVO 900X900MM 4650LM PLX II IP41 BLACK 830 (50W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	703850
Ingress protection:	IP41
Nominal power [W]:	50
Luminous flux [lm]*:	4650
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	F
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	900/900/120

CHARACTERISTICS

Suspended, square LED fitting with very high luminous flux, made of steel sheet, powder-coated grey, white, black. equipped with energy-saving light source LED-GO!. Opal PMMA diffuser ensures even light distribution and no glare effect.

APPLICATION

Suspended luminaire intended for indoor use in offices or common rooms. Suitable as a general light source in representative rooms.

MADERA ALTUS LED EVO 900X900MM 4650LM PLX II IP41 BLACK 830 (50W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	703850	Ingress protection:	IP41
Nominal power [W]:	50	Net weight [kg]:	20
Luminous flux [lm]:	4650	Category type:	louvres
Energy efficiency class:	F	Luminaire rated power P_{min} [W]:	50
Electrical protection class:	II	ETIM class:	EC002892
Colour temperature [K]:	3000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour rendering index:	>80	CE certificate:	225/2023
SDCM:	≤ 3	Warranty [years]:	2
Colour of the body:	black	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	900/900/120		

Card creation date: 08 April 2019

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 225/2023