

# MITRA LED 1700LM 4000K MAT IP66 II KL. (13W)

DETAILED CARD



## TECHNICAL PARAMETERS

Light source:	LED module
Ingress protection:	IP66
Nominal power [W]:	13
Luminous flux [lm]*:	1700
Colour temperature [K]:	4000
SDCM:	≤ 3
Colour rendering index:	80
Electrical protection class:	II
Energy efficiency class:	C
Material of the body:	PP+FG

## CHARACTERISTICS

LED fitting with high luminous efficiency and an energy-saving, integrated LED panel. Body made of polypropylene (PP) with glass fiber (GF), aluminum handle and polycarbonate diffuser (PC).

The lamp is available in two versions of light distribution:

- general G1 - with a frosted diffuser,
- road RM1 - with a transparent diffuser and directional lens matrices made of PMMA.

IP66 ingress protection class and IK07 impact-rating features make this fitting shock-resistant (vandal-resistant). The integrated handle allows for top mounting to the pole. Colour of the body: gray (RAL 7010).

Standard equipped with:

- surge protection (SP10kV),
- H07RN-F cable with a length of 0.6 m and an IP66 quick connection.

## APPLICATION

Fitting used in open spaces to lighten: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and mounting: post-top mounting. Mounting grip integrated with the fitting.

# MITRA LED 1700LM 4000K MAT IP66 II KL. (13W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	956232	Colour of the body:	grey
EAN:	5905963956232	Dimensions (H/W/T/S) [mm]:	398/398/175
Light source:	LED module	Mounting dimensions [mm]:	398/398/174
Nominal power [W]:	13	Ingress protection:	IP66
Rated power of the luminaire [W]:	12	Working temperature [°C]:	from -15 to +35
Supply voltage [V]:	220-240	Dimensions of single box [mm]:	400/400/175
Frequency [Hz]:	50 - 60	Net weight [kg]:	1.800
Luminous flux [lm]:	1700	Warranty [years]:	5
Luminous efficacy [lm/W]:	140	Category type:	Park and city lighting
Energy efficiency class:	C	Light distribution type:	G1
Electrical protection class:	II	Category of application:	parkings and bicycle paths
Colour temperature [K]:	4000	Ring colour:	grey
Colour rendering index:	80	Gross weight [kg]:	1.800
SDCM:	≤ 3	Permeability factor of the diffuser:	0.80
Power factor:	0.95	ETIM class:	EC000062
LED lifespan L70B50 [h]:	90000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Surge protection [kV]:	2	ULOR:	0%
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	frozen	CE certificate:	<a href="#">38/2024</a>
Diffuser colour:	transparent	Manual:	<a href="#">Download PDF</a>
Material of the body:	PP+FG	Plik LDT:	<a href="#">Download</a>

## LIGHT CURVES



# MITRA LED 1700LM 4000K MAT IP66 II KL. (13W)

DETAILED CARD

## TECHNICAL DETAILS



MITRA LED



MITRA LED

Card creation date: 04 June 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 38/2024



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl