MITRA LED 6450LM 4000K RM1 IP66 I KL. (52W)

DETAILED CARD





LED module
IP66
52
6450
4000
3
80
I
D
PP+FG



LED fitting with high luminous efficiency and an energy-saving, integrated LED panel. Body made of polypropylene (PP) with glass fiber (GF), aluminum handle and polycarbonate diffuser (PC).

The lamp is available in two versions of light distribiution:

- general G1 with a frozen diffuser,
- road RM1 with a transparent diffuser and directional lens matrices made of PMMA.

IP66 ingress protection class and IK07 impact-rating features make this fitting shock-resistant (vandal-resistant). The integrated handle allows for top mounting to the pole. Colour of the body: gray (RAL 7010).

Standard equipped with:

- surge protection (SP10kV),
- H07RN-F cable with a length of 0.6 m and an IP66 quick connection.

APPLICATION

Fitting used in open spaces to lighten: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and mounting: post-top mounting. Mounting grip integrated with the fitting.



MITRA LED 6450LM 4000K RM1 IP66 I KL. (52W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

956010
5905963956010
LED module
52
51.30
220-240
50 - 60
6450
126
D
I
4000
80
3
0.97
90000
2
PC
transparent
transparent
PMMA
matrix lens
PP+FG

	•
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	398/398/175
Mounting dimensions [mm]:	398/398/174
Ingress protection:	IP66
Working temperature [°C]:	from -15 to +35
Dimensions of single box [mm]:	400/400/175
Net weight [kg]:	48
Warranty [years]:	5
Category type:	Park and city lighting
Light distribution type:	RM1
Category of application:	parkings and bicycle paths
Beam angle [°]:	50000
Ring colour:	grey
Gross weight [kg]:	2.100
Permeability factor of the diffuser:	0.80
ETIM class:	EC000062
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
ULOR:	0%
Warranty [years]:	5
CE certificate:	100/2023
Manual:	Download PDF
Plik LDT:	Download

LIGHT CURVES







MITRA LED 6450LM 4000K RM1 IP66 I KL. (52W)

DETAILED CARD

TECHNICAL DETAILS







MITRA LED MITRA LED MITRA LED

Card creation date: 04 June 2025

 $The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer. \\ ^* Parameter tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10\% and (a) a constitute an offer tolerance is +/- 10$

