

MITRA LED 6450LM 4000K RM1 IP66 I KL. (52W)

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Ingress protection:	IP66
Nominal power [W]:	52
Luminous flux [lm]*:	6450
Colour temperature [K]:	4000
SDCM:	3
Color rendering index (Ra) >:	80
Electrical protection class:	I
Energy efficiency class:	D
Material of the body:	PP+FG

CHARACTERISTICS

LED fitting with high luminous efficiency and an energy-saving, integrated LED panel. Body made of polypropylene (PP) with glass fiber (GF), aluminum handle and polycarbonate diffuser (PC). The lamp is available in two versions of light distribution:
- general G1 - with a frosted diffuser,
- road RM1 - with a transparent diffuser and directional lens matrices made of PMMA.
IP66 ingress protection class and IK07 impact-rating features make this fitting shock-resistant (vandal-resistant). The integrated handle allows for top mounting to the pole. Colour of the body: gray (RAL 7010).
Standard equipped with:
- surge protection (SP10kV),
- H07RN-F cable with a length of 0.6 m and an IP66 quick connection.

APPLICATION

Fitting used in open spaces to lighten: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and mounting: post-top mounting. Mounting grip integrated with the fitting.


MITRA LED 6450LM 4000K RM1 IP66 I KL. (52W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	956010	Colour of the body:	grey
EAN:	5905963956010	Dimensions (H/W/T/S) [mm]:	398/398/175
Light source:	LED module	Mounting dimensions [mm]:	398/398/174
Nominal power [W]:	52	Ingress protection:	IP66
Rated power of the luminaire [W]:	51.30	Working temperature [°C]:	from -15 to +35
Supply voltage [V]:	220-240	Dimensions of single box [mm]:	400/400/175
Frequency [Hz]:	50 - 60	Net weight [kg]:	48
Luminous flux [lm]:	6450	Warranty [years]:	5
Luminous efficacy [lm/W]:	126	Category type:	Park and city lighting
Energy efficiency class:	D	Light distribution type:	RM1
Electrical protection class:	I	Category of application:	parkings and bicycle paths
Colour temperature [K]:	4000	Beam angle [°]:	50000
Color rendering index (Ra) >:	80	Ring colour:	grey
SDCM:	3	Gross weight [kg]:	2.100
Power factor:	0.97	Permeability factor of the diffuser:	0.80
LED lifespan L70B50 [h]:	90000	ETIM class:	EC000062
Surge protection [kV]:	2	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	PC	ULOR:	0%
Diffuser type:	transparent	Warranty [years]:	5
Diffuser colour:	transparent	CE certificate:	100/2023
Optics material:	PMMA	Manual:	Download PDF
Optics:	matrix lens	Plik LDT:	Download
Material of the body:	PP+FG		


LIGHT CURVES



MITRA LED 6450LM 4000K RM1 IP66 I KL. (52W)

DETAILED CARD


TECHNICAL DETAILS



MITRA LED



MITRA LED



MITRA LED

Card creation date: 04 June 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 100/2023