

PROXIMA LED EVO PLUS 3300LM 840 IP65/IP54 I KL. DALI OPAL (28W) 390MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	462108
Ingress protection:	IP65/54
Impact resistance:	IK10
Nominal power [W]:	28
Luminous flux [lm]*:	3300
Colour temperature [K]:	4000
Energy efficiency class:	E
Material of the body:	PP+T
Ring material:	ABS

CHARACTERISTICS

Surface-mounted, round LED ceiling lamp, fitted with an integrated, energy-saving LED features high luminous efficiency and high tightness. Its base and ring are made of UV-resistant plastic. Specially shaped diffuser made of impact-resistant PC provides the frame with the highest degree of impact resistance. This ceiling fixture is also available in the variant with a radio motion sensor and a 3h emergency module with a self-test.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor,
- with a radio motion sensor and DALI,
- corridor variant with DALI,
- DALI Swich DIMM,
- with 3h emergency module with self-test.

APPLICATION

Surface-mounted luminaire for ceiling or wall mounting is intended for outdoor use as façade lighting, or indoors: in rooms with high humidity and in passageways. Also available in a variant with a radio motion sensor, particularly recommended for use in utility rooms and passageways. It will also work well as a source of general light, also due to its additional decorative effect (distribution of indirect light on the assembly plane).


PROXIMA LED EVO PLUS 3300LM 840 IP65/IP54 I KL. DALI OPAL (28W) 390MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	462108	Mounting dimensions [mm]:	165/165
EAN:	5905963462108	Impact resistance:	IK10
Light source:	LED module	Ingress protection:	IP65/54
Nominal power [W]:	28	Mounting version:	surface
Rated power of the luminaire [W]:	31	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	DIMM DALI:	yes
Frequency [Hz]:	50 - 60	Dimensions of single box [mm]:	385/100/385
Luminous flux [lm]:	3300	Net weight [kg]:	1.300
Luminous efficacy [lm/W]:	107	Category type:	bulkheads
Energy efficiency class:	E	AC voltage range [V]:	220 - 240
Electrical protection class:	I	LED lifespan L70B50 [h]:	120000
Colour temperature [K]:	4000	LED lifespan L80B10 [h]:	75000
Color rendering index (Ra) >:	80	LED lifespan L90B10 [h]:	35000
Power factor:	0.91	Light distribution type:	lambertian
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	OPAL	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	PP+T	Warranty [years]:	5
Colour of the body:	white	CE certificate:	45/2022
Ring material:	ABS	Manual:	Download PDF
Ring colour:	white	Plik LDT:	Download
Dimensions (H/W/T/S) [mm]:	ø390/110		

LIGHT CURVES



Card creation date: 28 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 45/2022



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl