

PROXIMA LED EVO PLUS 390MM 1550LM 840 RCR WHITE (15W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	269639
Ingress protection:	IP65/54
Impact resistance:	IK10
Nominal power [W]:	15
Luminous flux [lm]*:	1538
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	PP
Ring material:	ABS

CHARACTERISTICS

Surface-mounted, round LED ceiling lamp, fitted with an integrated, energy-saving LED features high luminous efficiency and high tightness. Its base and ring are made of UV-resistant plastic. Specially shaped diffuser made of impact-resistant PC provides the frame with the highest degree of impact resistance. This ceiling fixture is also available in the variant with a radio motion sensor and a 3h emergency module with a self-test.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor,
- with a radio motion sensor and DALI,
- corridor variant with DALI,
- DALI Switch DIMM,
- with 3h emergency module with self-test.

APPLICATION

Surface-mounted luminaire for ceiling or wall mounting is intended for outdoor use as façade lighting, or indoors: in rooms with high humidity and in passageways. Also available in a variant with a radio motion sensor, particularly recommended for use in utility rooms and passageways. It will also work well as a source of general light, also due to its additional decorative effect (distribution of indirect light on the assembly plane).


PROXIMA LED EVO PLUS 390MM 1550LM 840 RCR WHITE (15W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Impact resistance:	IK10
Nominal power [W]:	15	Ingress protection:	IP65/54
Rated power of the luminaire [W]:	16.90	Mounting version:	surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Motion sensor:	yes
Luminous flux [lm]:	1538	Dimensions of single box [mm]:	100/390/390
Luminous efficacy [lm/W]:	91	Net weight [kg]:	1.350
Energy efficiency class:	F	Warranty [years]:	5
Electrical protection class:	I	CE certificate:	46/2022
Colour temperature [K]:	4000	Index:	269639
Colour rendering index:	80	EAN:	5905963269639
SDCM:	≤ 3	Category type:	bulkheads
Power factor:	0.90	Product line:	PROXIMA LED EVO PLUS
Max load (RCR) [W]:	400	AC voltage range [V]:	198 - 264
Beam angle [°]:	120	DC voltage range [V]:	176-276
Diffuser material:	PC	LED lifespan L70B50 [h]:	128000
Diffuser type:	OPAL	LED lifespan L80B20 [h]:	82000
Material of the body:	PP	LED lifespan L90B10 [h]:	41000
Colour of the body:	white	ETIM class:	EC002892
Ring material:	ABS	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Ring colour:	white	Warranty [years]:	5
Dimensions (H/W/T/S) [mm]:	ø390/110	Manual:	Download PDF
Mounting dimensions [mm]:	165/165	Plik LDT:	Download

LIGHT CURVES



Card creation date:10 January 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 46/2022



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl