

PROXIMA LED EVO PLUS 390MM 2200LM 830 DALI (CORR) RCR WHITE (22W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	269943
Ingress protection:	IP65/54
Impact resistance:	IK10
Nominal power [W]:	22
Luminous flux [lm]*:	2200
Colour temperature [K]:	3000
SDCM:	3
Energy efficiency class:	F
Material of the body:	PP
Ring material:	ABS

CHARACTERISTICS

Surface-mounted, round LED ceiling lamp, fitted with an integrated, energy-saving LED features high luminous efficiency and high tightness. Its base and ring are made of UV-resistant plastic. Specially shaped diffuser made of impact-resistant PC provides the frame with the highest degree of impact resistance. This ceiling fixture is also available in the variant with a radio motion sensor and a 3h emergency module with a self-test.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor,
- with a radio motion sensor and DALI,
- corridor variant with DALI,
- DALI Swich DIMM,
- with 3h emergency module with self-test.

APPLICATION

Surface-mounted luminaire for ceiling or wall mounting is intended for outdoor use as façade lighting, or indoors: in rooms with high humidity and in passageways. Also available in a variant with a radio motion sensor, particularly recommended for use in utility rooms and passageways. It will also work well as a source of general light, also due to its additional decorative effect (distribution of indirect light on the assembly plane).

PROXIMA LED EVO PLUS 390MM 2200LM 830 DALI (CORR) RCR WHITE (22W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	269943	Mounting dimensions [mm]:	165/165
EAN:	5905963269943	Impact resistance:	IK10
Light source:	LED module	Ingress protection:	IP65/54
Nominal power [W]:	22	Mounting version:	surface
Rated power of the luminaire [W]:	24.40	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Corridor function:	yes
Frequency [Hz]:	50 - 60	Motion sensor:	yes
Luminous flux [lm]:	2200	DIMM DALI:	yes
Luminous efficacy [lm/W]:	90	Dimensions of single box [mm]:	100/390/390
Energy efficiency class:	F	Net weight [kg]:	1.600
Electrical protection class:	I	Category type:	bulkheads
Colour temperature [K]:	3000	Product line:	PROXIMA LED EVO PLUS
Color rendering index (Ra) >:	80	AC voltage range [V]:	198 - 264
SDCM:	3	DC voltage range [V]:	176-280
Power factor:	0.90	LED lifespan L70B50 [h]:	128000
Max load (RCR) [W]:	400	LED lifespan L80B10 [h]:	82000
Beam angle [°]:	120	LED lifespan L90B10 [h]:	41000
Diffuser material:	PC	ETIM class:	EC002892
Diffuser type:	OPAL	Warranty [years]:	5
Material of the body:	PP	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	white	Warranty [years]:	5
Ring material:	ABS	CE certificate:	46/2022
Ring colour:	white	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	ø390/110	Pliik LDT:	Download

LIGHT CURVES



Card creation date: 28 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 46/2022



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl