

PROXIMA LED EVO PLUS 390MM 2200LM 830 DALI RCR WHITE (22W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	269905
Ingress protection:	IP65/54
Impact resistance:	IK10
Nominal power [W]:	22
Luminous flux [lm]*:	2200
Colour temperature [K]:	3000
SDCM:	3
Energy efficiency class:	F
Material of the body:	PP
Ring material:	ABS

CHARACTERISTICS

Surface-mounted, round LED ceiling lamp, fitted with an integrated, energy-saving LED features high luminous efficiency and high tightness. Its base and ring are made of UV-resistant plastic. Specially shaped diffuser made of impact-resistant PC provides the frame with the highest degree of impact resistance. This ceiling fixture is also available in the variant with a radio motion sensor and a 3h emergency module with a self-test.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor,
- with a radio motion sensor and DALI,
- corridor variant with DALI,
- DALI Switch DIMM,
- with 3h emergency module with self-test.

APPLICATION

Surface-mounted luminaire for ceiling or wall mounting is intended for outdoor use as façade lighting, or indoors: in rooms with high humidity and in passageways. Also available in a variant with a radio motion sensor, particularly recommended for use in utility rooms and passageways. It will also work well as a source of general light, also due to its additional decorative effect (distribution of indirect light on the assembly plane).


PROXIMA LED EVO PLUS 390MM 2200LM 830 DALI RCR WHITE (22W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	269905	Mounting dimensions [mm]:	165/165
EAN:	5905963269905	Impact resistance:	IK10
Light source:	LED module	Ingress protection:	IP65/54
Nominal power [W]:	22	Mounting version:	surface
Rated power of the luminaire [W]:	24.40	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220-240	Motion sensor:	yes
Frequency [Hz]:	50 - 60	DIMM DALI:	yes
Luminous flux [lm]:	2200	Dimensions of single box [mm]:	100/390/390
Luminous efficacy [lm/W]:	90	Net weight [kg]:	1.600
Energy efficiency class:	F	Category type:	bulkheads
Electrical protection class:	I	Product line:	PROXIMA LED EVO PLUS
Colour temperature [K]:	3000	AC voltage range [V]:	198 - 264
Color rendering index (Ra) >:	80	DC voltage range [V]:	176-280
SDCM:	3	LED lifespan L70B50 [h]:	128000
Power factor:	0.90	LED lifespan L80B20 [h]:	82000
Max load (RCR) [W]:	400	LED lifespan L90B10 [h]:	41000
Beam angle [°]:	120	ETIM class:	EC002892
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	OPAL	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	PP	Warranty [years]:	5
Colour of the body:	white	CE certificate:	46/2022
Ring material:	ABS	Manual:	Download PDF
Ring colour:	white	Plik LDT:	Download
Dimensions (H/W/T/S) [mm]:	ø390/110		

LIGHT CURVES



Card creation date: 28 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).  Certificate CE - Nr: 46/2022