

PROXIMA LED EVO PLUS 390MM 2350LM 840 DALI WHITE (22W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	269875
Ingress protection:	IP65/54
Impact resistance:	IK10
Nominal power [W]:	22
Luminous flux [lm]*:	2350
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	PP
Ring material:	ABS

CHARACTERISTICS

Surface-mounted, round LED ceiling lamp, fitted with an integrated, energy-saving LED features high luminous efficiency and high tightness. Its base and ring are made of UV-resistant plastic. Specially shaped diffuser made of impact-resistant PC provides the frame with the highest degree of impact resistance. This ceiling fixture is also available in the variant with a radio motion sensor and a 3h emergency module with a self-test.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor,
- with a radio motion sensor and DALI,
- corridor variant with DALI,
- DALI Switch DIMM,
- with 3h emergency module with self-test.

APPLICATION

Surface-mounted luminaire for ceiling or wall mounting is intended for outdoor use as façade lighting, or indoors: in rooms with high humidity and in passageways. Also available in a variant with a radio motion sensor, particularly recommended for use in utility rooms and passageways. It will also work well as a source of general light, also due to its additional decorative effect (distribution of indirect light on the assembly plane).


PROXIMA LED EVO PLUS 390MM 2350LM 840 DALI WHITE (22W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	22	Dimensions (H/W/T/S) [mm]:	ø390/110
Light source:	LED module	Mounting dimensions [mm]:	165/165
Colour temperature [K]:	4000	Impact resistance:	IK10
Luminous flux [lm]:	2350	Ingress protection:	IP65/54
Rated power of the luminaire [W]:	23.30	Mounting version:	surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Diffuser type:	OPAL	Dimensions of single box [mm]:	100/390/390
Frequency [Hz]:	50 - 60	Net weight [kg]:	1.550
DIMM DALI:	yes	Warranty [years]:	5
Luminous efficacy [lm/W]:	101	CE certificate:	46/2022
Energy efficiency class:	E	Index:	269875
Electrical protection class:	I	EAN:	5905963269875
Colour rendering index:	>80	Category type:	bulkheads
SDCM:	≤ 3	Product line:	PROXIMA LED EVO PLUS
Power factor:	0.90	AC voltage range [V]:	198 - 264
Beam angle [°]:	120	DC voltage range [V]:	176-280
Diffuser material:	PC	LED lifespan L70B50 [h]:	128000
Material of the body:	PP	LED lifespan L80B20 [h]:	82000
Colour of the body:	white	LED lifespan L90B10 [h]:	41000
Ring material:	ABS	ETIM class:	EC002892
Ring colour:	white	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
		Warranty [years]:	5
		Manual:	Download PDF
		Plik LDT:	Download

LIGHT CURVES



Card creation date:10 January 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 46/2022



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl