

TIARA LED M 9150LM 757 RM3 IP66 II CL. DALI SP10KV (72W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	955808
Ingress protection:	IP66
Impact resistance:	IK09
Luminaire rated power P_{min} [W]:	72
Luminous flux [lm]*:	9150
Colour temperature [K]:	5700
SDCM:	≤ 5
Colour rendering index:	> 70
Electrical protection class:	II
Material of the body:	powder coated aluminium

CHARACTERISTICS

TIARA LED is a new generation of road luminaires dedicated to LED technology. Designed from scratch, it introduces new solutions to improve light distribution and temperature balance, thus introducing new standards in road lighting. The luminaire uses directional lenticular matrices made of PMMA or PC, thanks to which it is possible to obtain a light distribution meeting the lighting classes defined in the PN-EN 13201: 2007 standard. Components of renowned manufacturers and new LED they have an effect on very high luminous efficiency - close to 130 lm / W. The luminaire uses a solution that integrates the diffuser with the LED module. The body and the handle are made of a pressure cast aluminum. The whole has been powder coated in gray (RAL9006). The luminaire design allows for tool-free access to the electrical equipment compartment. The luminaire is characterized by a very high degree of protection IP66 and resistance to mechanical impacts IK09 (vandal resistance). The fitting has many improvements to facilitate and accelerate assembly: an independent body with an ergonomic suspension system of the light module; handle adjustable in increments: -5° to +15° (peak to pole); -15° to +5° (side to boom). Lamp compatible with modern control systems (additional NEMA and ZHAGA connectors).

Standard equipment: protection against accidental overheating of the NTC fitting; overvoltage protection up to 10kV; fully programmable DALI driver; hardened glass.

APPLICATION

Streetlight fitting used in open spaces to lighten: streets, local roads, bicycle paths, alleys, pavements, car parks and squares. Installation and mounting: lateral side entry, post-top mounting. Mounting grip integrated with the fitting.

TIARA LED M 9150LM 757 RM3 IP66 II CL. DALI SP10KV (72W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Mounting version:	Top, on pole / Side, on boom
Rated power of the luminaire [W]:	72	Working temperature [°C]:	from -40 to +50
Supply voltage [V]:	220 - 240	Beam angle adjustment [°]:	-5 to +15 (peak); -15 to +5 (side)
Frequency [Hz]:	50 - 60	Lateral surface (SCx) [m2]:	0.028
Luminous flux [lm]:	9150	DIMM DALI:	yes
Luminous efficacy [lm/W]:	127	Protection type:	NTC
Energy efficiency class:	D	Net weight [kg]:	5.200
Electrical protection class:	II	Index:	955808
Colour temperature [K]:	5700	EAN:	5905963955808
Colour rendering index:	> 70	Category type:	street lighting
SDCM:	≤ 5	Version:	M
Surge protection [kV]:	10	Luminaire rated power P_{min} [W]:	72
Diffuser material:	toughened glass	AC voltage range [V]:	198 - 264
Diffuser type:	transparent	DC voltage range [V]:	186 - 250
Optics material:	PMMA	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Optics:	RM3	LED lifespan L90B10 [h]:	100000
Material of the body:	powder coated aluminium	ETIM class:	EC000062
Colour of the body:	grey	ULOR:	0%
Dimensions (H/W/T/S) [mm]:	665/122/262	CE certificate:	66/2020
Mounting dimensions [mm]:	ø60	ENEC Certificate:	0228/ENEC/20/M1
Impact resistance:	IK09	Warranty [years]:	10
Ingress protection:	IP66	Manual:	Download PDF

TIARA LED M 9150LM 757 RM3 IP66 II CL. DALI SP10KV (72W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
UL00184	mounting grip 78 mm TIARA LED
830UL109	Module CLUE CITY GATEWAY IP67 GSM



wall holder (galvanized) (314049)



wall holder (grey) (314056)



mounting grip 78 mm TIARA LED (UL00184)

Card creation date: 03 June 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 66/2020