

ASTER 1 LED 300MM 570LM 830 IP65 I CL. (8W) RAL 7037

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------------|-----------|
| Index: | 959585 |
| Ingress protection: | IP65 |
| Impact resistance: | IK10 |
| Rated power of the luminaire [W]*: | 8 |
| Luminous flux [lm]*: | 570 |
| Colour temperature [K]: | 3000 |
| Energy efficiency class: | G |
| Material of the body: | aluminium |
| Diffuser material: | PMMA |
| Diffuser type: | OPAL |

CHARACTERISTICS

Outdoor lamp for open spaces, with positive influence on the sense of security and aesthetic experience. The luminaires perform excellently on their own or as part of light installations, creating breathtaking light effects which enhance the exceptional ambience and decor of spaces.

APPLICATION

The oblong pole decors and lights: access roads to premises, pavements, paths, gardens, arbours, terraces.

ASTER 1 LED 300MM 570LM 830 IP65 I CL. (8W) RAL 7037

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|--------------------------------|------------------------------|
| Light source: | LED module | Dimensions (H/W/T/S) [mm]: | ø110/300 |
| Rated power of the luminaire [W]: | 8 | Impact resistance: | IK10 |
| Supply voltage [V]: | 220-240 | Ingress protection: | IP65 |
| Frequency [Hz]: | 50 - 60 | Dimensions of single box [mm]: | 185/315/180 |
| Luminous flux [lm]: | 570 | Net weight [kg]: | 3 |
| Energy efficiency class: | G | Warranty [years]: | 2 |
| Electrical protection class: | I | Index: | 959585 |
| Colour temperature [K]: | 3000 | EAN: | 5905963959585 |
| Beam angle [°]: | 360 | Category type: | accent lighting |
| Diffuser material: | PMMA | AC voltage range [V]: | 220 - 240 |
| Diffuser type: | OPAL | Power reducer: | yes |
| Material of the body: | aluminium | Luminous efficacy [lm/W]: | 71 |
| Colour of the body: | RAL7037 | Manual: | Download PDF |

Card creation date: 24 February 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 85/2019