ASTER 1 LED 550MM 570LM 830 IP65 I CL. (8W) RAL 7037

DETAILED CARD



TECHNICAL PARAMETERS

Index: 959561

Ingress protection: IP65

Impact resistance: IK10

Rated power of the luminaire [W]*: 8

Luminous flux [lm]*: 570

Colour temperature [K]: 3000

Energy efficiency class:

Material of the body: aluminium

Diffuser material: PMMA

Diffuser type: OPAL

CHARACTERISTICS

Outdoor lamp for open spaces, with positive influence on the sense of security and aesthetic experience. The luminaires perform excellently on their own or as part of light installations, creating breathtaking light effects which enhance the exceptional ambience and decor of spaces.

APPLICATION

The oblong pole decors and lights: access roads to premises, pavements, paths, gardens, arbours, terraces.



ASTER 1 LED 550MM 570LM 830 IP65 I CL. (8W) RAL 7037

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Rated power of the luminaire [W]:	8
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	570
Energy efficiency class:	G
Electrical protection class:	1
Colour temperature [K]:	3000
Beam angle [°]:	360
Diffuser material:	PMMA
Diffuser type:	OPAL
Material of the body:	aluminium
Colour of the body:	RAL7037

Dimensions (H/W/T/S) [mm]:	ø110/550
Impact resistance:	IK10
Ingress protection:	IP65
Dimensions of single box [mm]:	185/578/180
Net weight [kg]:	4.500
Warranty [years]:	2
Index:	959561
EAN:	5905963959561
Category type:	accent lighting
AC voltage range [V]:	220 - 240
Power reducer:	yes
Luminous efficacy [lm/W]:	71
Manual:	Download PDF

Card creation date: 24 February 2020



