

ASTER 1 LED 550MM 630LM 857 IP65 I CL. (8W) RAL 7037

DETAILED CARD



TECHNICAL PARAMETERS

Index:	x
Ingress protection:	IP65
Impact resistance:	IK10
Rated power of the luminaire [W]*:	8
Luminous flux [lm]*:	450 - 630
Colour temperature [K]:	3000; 4000; 5700
Energy efficiency class:	F; G
Material of the body:	aluminium
Diffuser material:	PMMA
Diffuser type:	OPAL

CHARACTERISTICS

Outdoor lamp for open spaces, with positive influence on the sense of security and aesthetic experience. The luminaires perform excellently on their own or as part of light installations, creating breathtaking light effects which enhance the exceptional ambience and decor of spaces.

APPLICATION

The oblong pole decors and lights: access roads to premises, pavements, paths, gardens, arbours, terraces.

ASTER 1 LED 550MM 630LM 857 IP65 I CL. (8W) RAL 7037

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	modu1 LED	Dimensions (H/W/T/S) [mm]:	ø110/300; ø110/550; ø110/800
Rated power of the luminaire [W]:	8	Impact resistance:	IK10
Supply voltage [V]:	220-240	Ingress protection:	IP65
Frequency [Hz]:	50-60	Dimensions of single box [mm]:	185/315/180; 185/578/180; 185/840/180
Luminous flux [lm]:	450 - 630	Net weight [kg]:	3
Energy efficiency class:	F; G	Warranty [years]:	2
Electrical protection class:	I	Index:	x
Colour temperature [K]:	3000; 4000; 5700	EAN:	x
Beam angle [°]:	180; 360	Category type:	accent lighting
Battery:	Nie	AC voltage range [V]:	220 - 240
Diffuser material:	PMMA	Power reducer:	yes
Diffuser type:	OPAL	Luminous efficacy [lm/W]:	66
Material of the body:	aluminium	Manual:	Download PDF
Colour of the body:	RAL7037		

Card creation date: 12 January 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 85/2019