

ASTER 1 LED 800MM 630LM 857 IP65 I CL. (8W) RAL 7037

DETAILED CARD



TECHNICAL PARAMETERS

Index:	959615
Ingress protection:	IP65
Impact resistance:	IK10
Rated power of the luminaire [W]*:	8
Luminous flux [lm]*:	630
Colour temperature [K]:	5700
Energy efficiency class:	F
Material of the body:	aluminium
Diffuser material:	PMMA
Diffuser type:	OPAL

CHARACTERISTICS

Outdoor lamp for open spaces, with positive influence on the sense of security and aesthetic experience. The luminaires perform excellently on their own or as part of light installations, creating breathtaking light effects which enhance the exceptional ambience and decor of spaces.

APPLICATION

The oblong pole decors and lights: access roads to premises, pavements, paths, gardens, arbours, terraces.

ASTER 1 LED 800MM 630LM 857 IP65 I CL. (8W) RAL 7037

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	ø110/800
Rated power of the luminaire [W]:	8	Impact resistance:	IK10
Supply voltage [V]:	220-240	Ingress protection:	IP65
Frequency [Hz]:	50 - 60	Dimensions of single box [mm]:	185/840/180
Luminous flux [lm]:	630	Net weight [kg]:	5.500
Energy efficiency class:	F	Warranty [years]:	2
Electrical protection class:	I	Index:	959615
Colour temperature [K]:	5700	EAN:	5905963959615
Beam angle [°]:	360	Category type:	accent lighting
Diffuser material:	PMMA	AC voltage range [V]:	220 - 240
Diffuser type:	OPAL	Power reducer:	yes
Material of the body:	aluminium	Luminous efficacy [lm/W]:	79
Colour of the body:	RAL7037	Manual:	Download PDF