

SPECTO LED 12W PRM 3000K 902MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	343766
Ingress protection:	IP40
Impact resistance:	IK02
Nominal power [W]:	12
Luminous flux [lm]*:	1150
Colour temperature [K]:	3000
Colour rendering index:	>80
Energy efficiency class:	A
Material of the body:	powder coated steel
Diffuser material:	PMMA

CHARACTERISTICS

Surface ceiling or wall mounted, high performance LED luminaire with compact space saving construction. Equipped with energy saving light sources LED. Powderpainted steel base, special multilayer prismatic diffuser combining high UV resistance PMMA cover and polypropylene optic system or single layer high UV resistance opal PMMA diffuser.

APPLICATION

Multi-purpose LED luminaire designed for indoor application for illuminating public use areas and corridors (administration buildings, schools and universities, health care buildings) Especially recommended for small space application or as complementary lighting. It is appropriate for new applications as well as replacing conventional T8 & T5 fittings on energy saving LED solutions. Fitting construction adapted for surface mounting (ceiling or wall) using included accessory installation kit.


SPECTO LED 12W PRM 3000K 902MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Colour of the body:	white
Nominal power [W]:	12	Dimensions (H/W/T/S) [mm]:	902/84/45
Supply voltage [V]:	220-240	Impact resistance:	IK02
Frequency [Hz]:	50 - 60	Ingress protection:	IP40
Luminous flux [lm]:	1150	Mounting version:	surface
Luminous efficacy [lm/W]:	96	Working temperature [°C]:	from -20 to +35
Energy efficiency class:	A	Net weight [kg]:	1.300
Electrical protection class:	I	Warranty [years]:	5
Colour temperature [K]:	3000	CE certificate:	54/2013
Colour rendering index:	>80	Index:	343766
Power factor:	0.90	EAN:	5905963343766
LED lifespan L70B50 [h]:	81000	Category type:	battens
Diffuser material:	PMMA	ETIM class:	EC000109
Diffuser type:	PRM	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	powder coated steel	Manual:	Download PDF

LIGHT CURVES



Card creation date: 28 May 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 54/2013



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl