


SPECTO LED 16W PRM 4000K 1252MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	x
Ingress protection:	IP40
Impact resistance:	IK02
Nominal power [W]:	8
Luminous flux [lm]*:	600 - 4400
Colour temperature [K]:	3000; 4000
Colour rendering index:	>80
Energy efficiency class:	A
Material of the body:	blacha stalowa malowana proszkowo
Diffuser material:	PMMA

CHARACTERISTICS

Surface ceiling or wall mounted, high performance LED luminaire with compact space saving construction. Equipped with energy saving light sources LED. Powderpainted steel base, special multilayer prismatic diffuser combining high UV resistance PMMA cover and polypropylene optic system or single layer high UV resistance opal PMMA diffuser.

APPLICATION

Multi-purpose LED luminaire designed for indoor application for illuminating public use areas and corridors (administration buildings, schools and universities, health care buildings) Especially recommended for small space application or as complementary lighting. It is appropriate for new applications as well as replacing conventional T8 & T5 fittings on energy saving LED solutions. Fitting construction adapted for surface mounting (ceiling or wall) using included accessory installation kit.


SPECTO LED 16W PRM 4000K 1252MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	moduł LED	Impact resistance:	IK02
Nominal power [W]:	8	Ingress protection:	IP40
Supply voltage [V]:	220-240	Mounting version:	natynkowy
Frequency [Hz]:	50-60	Working temperature [°C]:	od -20 do +35
Luminous flux [lm]:	600 - 4400	Motion sensor:	yes
Energy efficiency class:	A	DIMM DALI:	yes
Electrical protection class:	I	Switch:	yes
Colour temperature [K]:	3000; 4000	Warranty [years]:	5
Colour rendering index:	>80	CE certificate:	336/2023; 54/2013
Power factor:	0.90	Index:	x
LED lifespan L70B50 [h]:	50000; 81000	EAN:	x
Diffuser material:	PMMA	Category type:	battens
Diffuser type:	PRM; PRM MAT	ETIM class:	EC000109
Material of the body:	blacha stalowa malowana proszkowo	Photobiological safety:	grupa ryzyka 1 (niskie ryzyko)
Colour of the body:	biały	Warranty [years]:	2
Dimensions (H/W/T/S) [mm]:	1252/84/45; 1552/84/45; 642/84/45; 902/84/45	Manual:	Download PDF

LIGHT CURVES



Card creation date: 28 May 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 336/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl