

SPECTO LED 32W PRM 4000K 1252MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	343896
Ingress protection:	IP40
Impact resistance:	IK02
Nominal power [W]:	32
Luminous flux [lm]*:	3300
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	A
Material of the body:	powder coated steel
Diffuser material:	PMMA

CHARACTERISTICS

Surface ceiling or wall mounted, high performance LED luminaire with compact space saving construction. Equipped with energy saving light sources LED. Powderpainted steel base, special multilayer prismatic diffuser combining high UV resistance PMMA cover and polypropylene optic system or single layer high UV resistance opal PMMA diffuser.

APPLICATION

Multi-purpose LED luminaire designed for indoor application for illuminating public use areas and corridors (administration buildings, schools and universities, health care buildings) Especially recommended for small space application or as complementary lighting. It is appropriate for new applications as well as replacing conventional T8 & T5 fittings on energy saving LED solutions. Fitting construction adapted for surface mounting (ceiling or wall) using included accessory installation kit.


SPECTO LED 32W PRM 4000K 1252MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	32	Colour of the body:	white
Light source:	LED module	Impact resistance:	IK02
Colour temperature [K]:	4000	Ingress protection:	IP40
Luminous flux [lm]:	3300	Mounting version:	surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Diffuser type:	PRM	Net weight [kg]:	1.700
Frequency [Hz]:	50 - 60	Warranty [years]:	5
Luminous efficacy [lm/W]:	103	CE certificate:	336/2023
Energy efficiency class:	A	Index:	343896
Dimensions (H/W/T/S) [mm]:	1252/84/45	EAN:	5905963343896
Electrical protection class:	I	Category type:	battens
Colour rendering index:	>80	ETIM class:	EC000109
Power factor:	0.90	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L70B50 [h]:	81000	Manual:	Download PDF
Diffuser material:	PMMA	Plik LDT:	Download
Material of the body:	powder coated steel		

LIGHT CURVES



Card creation date: 12 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 336/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl