

CAPELLA LED PLUS BOX RING 340MM 1120LM IP65 840 ANTHRACITE (11W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	659966
Ingress protection:	IP65
Impact resistance:	IK07
Nominal power [W]:	11
Luminous flux [lm]*:	1120
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	ABS
Ring material:	ABS

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor.
- with a PIR presence detector,
- with DALI control,
- with CORRIDOR function (DALI + RCR),
- with Master / Slave RCR motion sensor (wireless),
- with emergency module,
- with very high ingress protection IP65,
- with ANTIVANDAL protection.

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

CAPELLA LED PLUS BOX RING 340MM 1120LM IP65 840 ANTHRACITE (11W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	11	Diffuser type:	OPAL
Light source:	LED module	Diffuser colour:	white
Colour temperature [K]:	4000	Optics material:	PMMA
Luminous flux [lm]:	1120	Optics:	lens
Rated power of the luminaire [W]:	11.90	Material of the body:	ABS
Supply voltage [V]:	220-240	Colour of the body:	white
Frequency [Hz]:	50 - 60	Ring material:	ABS
EDGE/BOX Colour:	anthracite	Mounting dimensions [mm]:	158
Ring colour:	anthracite	Impact resistance:	IK07
Version:	BOX RING IP65	Ingress protection:	IP65
Luminous efficacy [lm/W]:	95	Mounting version:	surface
Energy efficiency class:	E	Working temperature [°C]:	from -10 to +35
Electrical protection class:	II	Accessories included:	gland, extraction, 2x cover cable, screws, wall plugs 6mm
Colour rendering index:	>80	Dimensions of single box [mm]:	342/342/122
SDCM:	≤ 3	Net weight [kg]:	0.860
Power factor:	0.92	Warranty [years]:	5
Dimensions (H/W/T/S) [mm]:	340/105	CE certificate:	373/2023
LED lifespan L70B50 [h]:	122000	Index:	659966
Beam angle [°]:	120	Category type:	bulkheads
Surge protection [kV]:	1	Product line:	plus
Diffuser material:	PC	AC voltage range [V]:	220 - 240
		UGR (4H8H):	16,5-23,6
		Light distribution type:	lambertian
		Dimensions of bulk box (H/W/D) [mm]:	794/1194/982
		Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
		Manual:	Download PDF
		Plik LDT:	Download

Card creation date: 17 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 373/2023