

CAPELLA LED PLUS EDGE BOX 950LM 830 IP54 AW 3H BIAŁY (11W) 320MM

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|--------|
| Index: | 949210 |
| Ingress protection: | IP54 |
| Impact resistance: | IK06 |
| Nominal power [W]: | 11 |
| Luminous flux [lm]*: | 950 |
| Colour temperature [K]: | 3000 |
| SDCM: | ≤ 3 |
| Energy efficiency class: | F |
| Material of the body: | ABS |

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor,
- with a PIR presence detector,
- with DALI control,
- with CORRIDOR function (DALI + RCR),
- with Master / Slave RCR motion sensor (wireless),
- with emergency module,
- with very high ingress protection IP65,
- with ANTIVANDAL protection.

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

CAPELLA LED PLUS EDGE BOX 950LM 830 IP54 AW 3H BIAŁY (11W) 320MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|--------------------------------------|---|
| Light source: | LED module | Dimensions (H/W/T/S) [mm]: | 320/105 |
| Nominal power [W]: | 11 | Mounting dimensions [mm]: | 158 |
| Rated power of the luminaire [W]: | 11.90 | Impact resistance: | IK06 |
| Supply voltage [V]: | 220-240 | Ingress protection: | IP54 |
| Frequency [Hz]: | 50 - 60 | Mounting version: | surface |
| Luminous flux [lm]: | 950 | Working temperature [°C]: | from -10 to +35 |
| Luminous efficacy [lm/W]: | 80 | Emergency lighting [h]: | 3 |
| Energy efficiency class: | F | Accessories included: | gland, extraction, 2x cover cable, screws, wall plugs 6mm |
| Electrical protection class: | II | Dimensions of single box [mm]: | 342/342/122 |
| Colour temperature [K]: | 3000 | Net weight [kg]: | 1.500 |
| Colour rendering index: | >80 | Warranty [years]: | 2 / 0.5 (bateria) |
| SDCM: | ≤ 3 | CE certificate: | 373/2023 |
| Power factor: | 0.93 | Index: | 949210 |
| LED lifespan L70B50 [h]: | 122000 | EAN: | 5905963949210 |
| Beam angle [°]: | 120 | Category type: | bulkheads |
| Battery: | NiMh | Version: | EDGE BOX |
| Battery capacity [mAh]: | 1500 | Product line: | plus |
| Surge protection [kV]: | 1 | AC voltage range [V]: | 220 - 240 |
| Diffuser material: | PC | UGR (4H8H): | 16,1-24,2 |
| Diffuser type: | OPAL | Light distribution type: | lambertian |
| Diffuser colour: | white | Dimensions of bulk box (H/W/D) [mm]: | 794/1194/982 |
| Optics material: | PMMA | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Optics: | lens | EDGE/BOX Colour: | white |
| Material of the body: | ABS | Manual: | Download PDF |
| Colour of the body: | white | | |

LIGHT CURVES



Card creation date: 13 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 373/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl