

CAPELLA LED PLUS EDGE BOX 950LM 830 IP54 AW 3H BIAŁY (11W) 320MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	949210
Ingress protection:	IP54
Impact resistance:	IK06
Nominal power [W]:	11
Luminous flux [lm]*:	950
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	ABS

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor,
- with a PIR presence detector,
- with DALI control,
- with CORRIDOR function (DALI + RCR),
- with Master / Slave RCR motion sensor (wireless),
- with emergency module,
- with very high ingress protection IP65,
- with ANTIVANDAL protection.

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

CAPELLA LED PLUS EDGE BOX 950LM 830 IP54 AW 3H BIAŁY (11W) 320MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	11	Surge protection [kV]:	1
Light source:	LED module	Diffuser material:	PC
Colour temperature [K]:	3000	Diffuser type:	OPAL
Luminous flux [lm]:	950	Diffuser colour:	white
Rated power of the luminaire [W]:	11.90	Optics material:	PMMA
Supply voltage [V]:	220-240	Optics:	lens
Frequency [Hz]:	50 - 60	Material of the body:	ABS
EDGE/BOX Colour:	white	Colour of the body:	white
Version:	EDGE BOX	Mounting dimensions [mm]:	158
Luminous efficacy [lm/W]:	80	Impact resistance:	IK06
Energy efficiency class:	F	Ingress protection:	IP54
Electrical protection class:	II	Mounting version:	surface
Colour rendering index:	>80	Working temperature [°C]:	from -10 to +35
SDCM:	≤ 3	Accessories included:	gland, extraction, 2x cover cable, screws, wall plugs 6mm
Power factor:	0.93	Dimensions of single box [mm]:	342/342/122
Emergency lighting [h]:	3	Net weight [kg]:	1.500
Dimensions (H/W/T/S) [mm]:	320/105	Warranty [years]:	2 / 0.5 (bateria)
LED lifespan L70B50 [h]:	122000	CE certificate:	373/2023
Beam angle [°]:	120	Index:	949210
Battery:	NiMh	EAN:	5905963949210
Battery capacity [mAh]:	1500	Category type:	bulkheads
		Product line:	plus
		AC voltage range [V]:	220 - 240
		UGR (4H8H):	16,1-24,2
		Light distribution type:	lambertian
		Dimensions of bulk box (H/W/D) [mm]:	794/1194/982
		Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
		Manual:	Download PDF

LIGHT CURVES

