CAPELLA LED PLUS EDGE BOX 950LM 830 IP54 DALI BIAŁY (11W) 320MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	949685
Ingress protection:	IP54
Impact resistance:	IK06
Nominal power [W]:	11
Luminous flux [lm]*:	950
Colour temperature [K]:	3000
SDCM:	3
Energy efficiency class:	F
Material of the body:	ABS

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor.
- with a PIR presence detector,
- with DALI control,
- with CORRIDOR function (DALI + RCR),
- with Master / Slave RCR motion sensor (wireless),
- with emergency module,
- with very high ingress protection IP65,
- with ANTIVANDAL protection.

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.



CAPELLA LED PLUS EDGE BOX 950LM 830 IP54 DALI BIAŁY (11W) 320MM


DETAILED CARD

TECHNICAL PARAMETERS TABLE

LED module
11
11.90
220-240
50 - 60
950
80
F
II
3000
80
3
0.93
122000
120
1
PC
OPAL
white
PMMA
lens
ABS
white
320/105

Mounting dimensions [mm]:	158
Impact resistance:	IK06
Ingress protection:	IP54
Mounting version:	surface
Working temperature [°C]:	from -10 to +35
DIMM DALI:	yes
Accessories included:	gland, extraction, 2x cover cable, screws, wall plugs 6mm
Dimensions of single box [mm]:	342/342/122
Net weight [kg]:	0.850
Warranty [years]:	5
CE certificate:	<u>373/2023</u>
Index:	949685
EAN:	5905963949685
Category type:	bulkheads
Category type: Version:	bulkheads EDGE BOX
Version:	EDGE BOX
Version: Product line:	EDGE BOX plus
Version: Product line: AC voltage range [V]:	EDGE BOX plus 220 - 240
Version: Product line: AC voltage range [V]: UGR (4H8H):	EDGE BOX plus 220 - 240 16,1-24,2
Version: Product line: AC voltage range [V]: UGR (4H8H): Light distribution type:	EDGE BOX plus 220 - 240 16,1-24,2 lambertian
Version: Product line: AC voltage range [V]: UGR (4H8H): Light distribution type: Dimensions of bulk box (H/W/D) [mm]:	EDGE BOX plus 220 - 240 16,1-24,2 lambertian 794/1194/982 Risk Group 1 (no photobiological hazard under normal behavioral
Version: Product line: AC voltage range [V]: UGR (4H8H): Light distribution type: Dimensions of bulk box (H/W/D) [mm]: Photobiological safety:	EDGE BOX plus 220 - 240 16,1-24,2 lambertian 794/1194/982 Risk Group 1 (no photobiological hazard under normal behavioral limitation)

LIGHT CURVES



Card creation date: 27 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

