

CAPELLA LED PLUS EDGE BOX RING 1400LM 830 IP54 RCR SLAVE WHITE (15W) 340MM

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|--------|
| Index: | 948626 |
| Ingress protection: | IP54 |
| Impact resistance: | IK07 |
| Nominal power [W]: | 15 |
| Luminous flux [lm]*: | 1400 |
| Colour temperature [K]: | 3000 |
| SDCM: | 3 |
| Energy efficiency class: | F |
| Material of the body: | ABS |
| Ring material: | ABS |

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor,
- with a PIR presence detector,
- with DALI control,
- with CORRIDOR function (DALI + RCR),
- with Master / Slave RCR motion sensor (wireless),
- with emergency module,
- with very high ingress protection IP65,
- with ANTIVANDAL protection.

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

CAPELLA LED PLUS EDGE BOX RING 1400LM 830 IP54 RCR SLAVE WHITE (15W) 340MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|--------------------------------------|---|
| Light source: | LED module | Mounting dimensions [mm]: | 158 |
| Nominal power [W]: | 15 | Impact resistance: | IK07 |
| Rated power of the luminaire [W]: | 16 | Ingress protection: | IP54 |
| Supply voltage [V]: | 220-240 | Mounting version: | surface |
| Frequency [Hz]: | 50 - 60 | Working temperature [°C]: | from -10 to +35 |
| Luminous flux [lm]: | 1400 | Motion sensor: | yes |
| Luminous efficacy [lm/W]: | 88 | Accessories included: | gland, extraction, 2x cover cable, screws, wall plugs 6mm |
| Energy efficiency class: | F | Master/slave: | slave |
| Electrical protection class: | II | Dimensions of single box [mm]: | 342/342/122 |
| Colour temperature [K]: | 3000 | Net weight [kg]: | 1.400 |
| Color rendering index (Ra) >: | 80 | Warranty [years]: | 5 |
| SDCM: | 3 | CE certificate: | 373/2023 |
| Power factor: | 0.95 | Index: | 948626 |
| LED lifespan L70B50 [h]: | 115000 | EAN: | 5905963948626 |
| Beam angle [°]: | 120 | Category type: | bulkheads |
| Surge protection [kV]: | 1 | Version: | EDGE BOX RING |
| Diffuser material: | PC | Product line: | plus |
| Diffuser type: | OPAL | AC voltage range [V]: | 220 - 240 |
| Diffuser colour: | white | UGR (4H8H): | 17,5-25,2 |
| Optics material: | PMMA | Light distribution type: | lamertian |
| Optics: | lens | Dimensions of bulk box (H/W/D) [mm]: | 794/1194/982 |
| Material of the body: | ABS | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Colour of the body: | white | EDGE/BOX Colour: | white |
| Ring material: | ABS | Manual: | Download PDF |
| Ring colour: | white | Plik LDT: | Download |
| Dimensions (H/W/T/S) [mm]: | 340/105 | | |

LIGHT CURVES



CAPELLA LED PLUS EDGE BOX RING 1400LM 830 IP54 RCR SLAVE WHITE (15W) 340MM

DETAILED CARD
TECHNICAL DETAILS



CAPELLA LED EDGE

Card creation date: 27 October 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 373/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl