

CAPELLA LED PLUS EDGE BOX RING 1500LM 840 IP54 AW 3H BIAŁY (15W) 340MM

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|--------|
| Index: | 949364 |
| Ingress protection: | IP54 |
| Impact resistance: | IK07 |
| Nominal power [W]: | 15 |
| Luminous flux [lm]*: | 1500 |
| Colour temperature [K]: | 4000 |
| SDCM: | ≤ 3 |
| Energy efficiency class: | E |
| Material of the body: | ABS |
| Ring material: | ABS |

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor,
- with a PIR presence detector,
- with DALI control,
- with CORRIDOR function (DALI + RCR),
- with Master / Slave RCR motion sensor (wireless),
- with emergency module,
- with very high ingress protection IP65,
- with ANTIVANDAL protection.

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.


CAPELLA LED PLUS EDGE BOX RING 1500LM 840 IP54 AW 3H BIAŁY (15W) 340MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|--------------------------------------|---|
| Light source: | LED module | Ring colour: | white |
| Nominal power [W]: | 15 | Dimensions (H/W/T/S) [mm]: | 340/105 |
| Rated power of the luminaire [W]: | 16 | Mounting dimensions [mm]: | 158 |
| Supply voltage [V]: | 220-240 | Impact resistance: | IK07 |
| Frequency [Hz]: | 50 - 60 | Ingress protection: | IP54 |
| Luminous flux [lm]: | 1500 | Mounting version: | surface |
| Luminous efficacy [lm/W]: | 94 | Working temperature [°C]: | from -10 to +35 |
| Energy efficiency class: | E | Emergency lighting [h]: | 3 |
| Electrical protection class: | II | Accessories included: | gland, extraction, 2x cover cable, screws, wall plugs 6mm |
| Colour temperature [K]: | 4000 | Dimensions of single box [mm]: | 342/342/122 |
| Colour rendering index: | >80 | Net weight [kg]: | 1.320 |
| SDCM: | ≤ 3 | Warranty [years]: | 2 / 0.5 (bateria) |
| Power factor: | 0.94 | CE certificate: | 373/2023 |
| LED lifespan L70B50 [h]: | 115000 | Index: | 949364 |
| Beam angle [°]: | 120 | EAN: | 5905963949364 |
| Battery: | NiMh | Category type: | bulkheads |
| Battery capacity [mAh]: | 1500 | Version: | EDGE BOX RING |
| Surge protection [kV]: | 1 | Product line: | plus |
| Diffuser material: | PC | AC voltage range [V]: | 220 - 240 |
| Diffuser type: | OPAL | UGR (4H8H): | 17,5-25,2 |
| Diffuser colour: | white | Light distribution type: | lamertian |
| Optics material: | PMMA | Dimensions of bulk box (H/W/D) [mm]: | 794/1194/982 |
| Optics: | lens | ETIM class: | EC000109 |
| Material of the body: | ABS | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Colour of the body: | white | EDGE/BOX Colour: | white |
| Ring material: | ABS | Manual: | Download PDF |

LIGHT CURVES



CAPELLA LED PLUS EDGE BOX RING 1500LM 840 IP54 AW 3H BIAŁY (15W) 340MM

DETAILED CARD

TECHNICAL DETAILS



CAPELLA LED EDGE

Card creation date: 13 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 373/2023