

CAPELLA LED PLUS EDGE BOX RING 340MM 1400LM IP65 830 (15W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	950629
Ingress protection:	IP65
Impact resistance:	IK07
Nominal power [W]:	15
Luminous flux [lm]*:	1400
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	ABS
Ring material:	ABS

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor,
- with a PIR presence detector,
- with DALI control,
- with CORRIDOR function (DALI + RCR),
- with Master / Slave RCR motion sensor (wireless),
- with emergency module,
- with very high ingress protection IP65,
- with ANTIVANDAL protection.

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.

CAPELLA LED PLUS EDGE BOX RING 340MM 1400LM IP65 830 (15W)

DETAILED CARD


TECHNICAL PARAMETERS TABLE

Nominal power [W]:	15	Diffuser type:	OPAL
Light source:	LED module	Diffuser colour:	white
Colour temperature [K]:	3000	Optics material:	PMMA
Luminous flux [lm]:	1400	Optics:	lens
Rated power of the luminaire [W]:	16	Material of the body:	ABS
Supply voltage [V]:	220-240	Colour of the body:	white
Frequency [Hz]:	50 - 60	Ring material:	ABS
EDGE/BOX Colour:	white	Mounting dimensions [mm]:	158
Ring colour:	white	Impact resistance:	IK07
Version:	EDGE BOX RING IP65	Ingress protection:	IP65
Luminous efficacy [lm/W]:	88	Mounting version:	surface
Energy efficiency class:	F	Working temperature [°C]:	from -10 to +35
Electrical protection class:	II	Accessories included:	gland, extraction, 2x cover cable, screws, wall plugs 6mm
Colour rendering index:	>80	Dimensions of single box [mm]:	342/342/122
SDCM:	≤ 3	Net weight [kg]:	1,100
Power factor:	0.95	Warranty [years]:	5
Dimensions (H/W/T/S) [mm]:	340/105	CE certificate:	373/2023
LED lifespan L70B50 [h]:	115000	Index:	950629
Beam angle [°]:	120	EAN:	5905963950629
Surge protection [kV]:	1	Category type:	bulkheads
Diffuser material:	PC	Product line:	plus
		AC voltage range [V]:	220 - 240
		UGR (4H8H):	17,5-25,2
		Light distribution type:	lambertian
		Dimensions of bulk box (H/W/D) [mm]:	794/1194/982
		Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
		Manual:	Download PDF
		Pliik LDT:	Download

LIGHT CURVES

CAPELLA LED PLUS EDGE BOX RING 340MM 1400LM IP65 830 (15W)

DETAILED CARD



TECHNICAL DETAILS



CAPELLA LED EDGE

Card creation date: 17 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 373/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl