


CAPELLA LED PLUS EDGE BOX RING 340MM 950LM IP54 830 (11W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	949319
Ingress protection:	IP54
Impact resistance:	IK07
Nominal power [W]:	11
Luminous flux [lm]*:	950
Colour temperature [K]:	3000
SDCM:	3
Energy efficiency class:	F
Material of the body:	ABS
Ring material:	ABS

CHARACTERISTICS

CAPELLA LED is a wide line of luminaires combining high aesthetic values and lighting parameters. The body has been made from ABS and the frosted diffuser from impact-resistant polycarbonate (PC). A multitude of versions makes it possible to adapt the luminaire to many non-standard applications.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor,
- with a PIR presence detector,
- with DALI control,
- with CORRIDOR function (DALI + RCR),
- with Master / Slave RCR motion sensor (wireless),
- with emergency module,
- with very high ingress protection IP65,
- with ANTIVANDAL protection.

APPLICATION

Surface-mounted wall or ceiling luminaire intended for indoor use (utility rooms, staircases, circulation routes). It is also available in a version with an RF motion detector which is especially recommended for use in spaces open to the public.


CAPELLA LED PLUS EDGE BOX RING 340MM 950LM IP54 830 (11W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	340/105
Nominal power [W]:	11	Mounting dimensions [mm]:	158
Rated power of the luminaire [W]:	11.90	Impact resistance:	IK07
Supply voltage [V]:	220-240	Ingress protection:	IP54
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous flux [lm]:	950	Working temperature [°C]:	from -10 to +35
Luminous efficacy [lm/W]:	80	Accessories included:	gland, extraction, 2x cover cable, screws, wall plugs 6mm
Energy efficiency class:	F	Dimensions of single box [mm]:	342/342/122
Electrical protection class:	II	Net weight [kg]:	0.990
Colour temperature [K]:	3000	Warranty [years]:	5
Color rendering index (Ra) >:	80	CE certificate:	373/2023
SDCM:	3	Index:	949319
Power factor:	0.93	EAN:	5905963949319
LED lifespan L70B50 [h]:	122000	Category type:	bulkheads
Beam angle [°]:	120	Version:	EDGE BOX RING
Surge protection [kV]:	1	Product line:	plus
Diffuser material:	PC	AC voltage range [V]:	220 - 240
Diffuser type:	OPAL	UGR (4H8H):	16,1-24,2
Diffuser colour:	white	Light distribution type:	lambertian
Optics material:	PMMA	Dimensions of bulk box (H/W/D) [mm]:	794/1194/982
Optics:	lens	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	ABS	EDGE/BOX Colour:	white
Colour of the body:	white	Manual:	Download PDF
Ring material:	ABS	Pliik LDT:	Download
Ring colour:	white		

LIGHT CURVES



CAPELLA LED PLUS EDGE BOX RING 340MM 950LM IP54 830 (11W)

DETAILED CARD

TECHNICAL DETAILS



CAPELLA LED EDGE

Card creation date: 27 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 373/2023