

# DEIMOS LED PLUS 2200LM 830 IP40 I KL. AW 3H AT CZARNY 20W 400MM

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	657177
Ingress protection:	IP40
Nominal power [W]:	20
Luminous flux [lm]*:	2200
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	HIPS
Diffuser material:	PMMA
Diffuser type:	OPAL

## CHARACTERISTICS

Surface mounted, round LED fitting with very high diffuser diameter, high luminous flux and even light distribution. Includes an integrated energy-saving light source LED GO!. HIPS base, powder coated white and black; light, white diffuser made using termoforming method. Simple pawl-based mounting system does not require any additional tools. The luminaire may be used to replace standard four-lamp fittings in irregular shaped rooms.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- radio motion sensor,
- corridor function,
- DALI,
- emergency module.

## APPLICATION

Surface mounted fitting intended for indoor use characterized by even light distribution and good surface lighting. Particularly suitable as a general light source in representative rooms and passageways. Thanks to exceptional lighting parameters, possible integration with the DALI system and decorative qualities, the product will surely prove its worth in large conference halls.

# DEIMOS LED PLUS 2200LM 830 IP40 I KL. AW 3H AT CZARNY 20W 400MM

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Mounting dimensions [mm]:	306/308
Nominal power [W]:	20	Ingress protection:	IP40
Rated power of the luminaire [W]:	26	Mounting version:	surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Emergency lighting [h]:	3
Luminous flux [lm]:	2200	Accessories included:	mounting pins
Luminous efficacy [lm/W]:	85	Protection type:	fuse
Energy efficiency class:	F	Dimensions of single box [mm]:	445/445/102
Electrical protection class:	I	Net weight [kg]:	1.800
Colour temperature [K]:	3000	Warranty [years]:	2 / 0.5 (bateria)
Colour rendering index:	80	CE certificate:	<a href="#">390/2023</a>
SDCM:	≤ 3	Index:	657177
Power factor:	0.30	EAN:	5905963657177
Beam angle [°]:	131	Category type:	bulkheads
Battery:	NiMh	Autotest:	yes
Battery capacity [mAh]:	2100	Operating mode:	M
Diffuser material:	PMMA	Luminaire rated power $\Phi_{min}$ [W]:	26.50
Diffuser type:	OPAL	AC voltage range [V]:	220-240
Diffuser colour:	white	UGR (4H8H):	16,1-24,1
Optics material:	PMMA	Light distribution type:	lambertian
Optics:	lens	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	HIPS	Impact resistance:	IK02
Colour of the body:	black	Manual:	<a href="#">Download PDF</a>
Dimensions (H/W/T/S) [mm]:	ø400/100		

## LIGHT CURVES



Card creation date:10 January 2025  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 390/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)