

DEIMOS LED PLUS 2350LM 840 IP40 I KL. DALI CZARNY 20W 400MM

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---------------------------------|--------|
| Index: | 657269 |
| Ingress protection: | IP40 |
| Nominal power [W]: | 20 |
| Luminous flux [lm]*: | 2350 |
| Colour temperature [K]: | 4000 |
| SDCM: | ≤ 3 |
| Energy efficiency class: | E |
| Material of the body: | HIPS |
| Diffuser material: | PMMA |
| Diffuser type: | OPAL |

CHARACTERISTICS

Surface mounted, round LED fitting with very high diffuser diameter, high luminous flux and even light distribution. Includes an integrated energy-saving light source LED GO!. HIPS base, powder coated white and black; light, white diffuser made using thermoforming method. Simple pawl-based mounting system does not require any additional tools. The luminaire may be used to replace standard four-lamp fittings in irregular shaped rooms.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- radio motion sensor,
- corridor function,
- DALI,
- emergency module.

APPLICATION

Surface mounted fitting intended for indoor use characterized by even light distribution and good surface lighting. Particularly suitable as a general light source in representative rooms and passageways. Thanks to exceptional lighting parameters, possible integration with the DALI system and decorative qualities, the product will surely prove its worth in large conference halls.

DEIMOS LED PLUS 2350LM 840 IP40 I KL. DALI CZARNY 20W 400MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------|--------------------------------------|---|
| Nominal power [W]: | 20 | Optics material: | PMMA |
| Light source: | LED module | Optics: | lens |
| Colour temperature [K]: | 4000 | Material of the body: | HIPS |
| Luminous flux [lm]: | 2350 | Dimensions (H/W/T/S) [mm]: | ø400/100 |
| Rated power of the luminaire [W]: | 25 | Mounting dimensions [mm]: | 306/313 |
| Supply voltage [V]: | 220-240 | Ingress protection: | IP40 |
| Diffuser type: | OPAL | Mounting version: | surface |
| Frequency [Hz]: | 50 - 60 | Working temperature [°C]: | from -20 to +35 |
| DIMM DALI: | yes | Accessories included: | mounting pins |
| Luminous efficacy [lm/W]: | 94 | Dimensions of single box [mm]: | 445/445/107 |
| Energy efficiency class: | E | Net weight [kg]: | 1.600 |
| Electrical protection class: | I | Warranty [years]: | 5 |
| Colour of the body: | black | CE certificate: | 390/2023 |
| Colour rendering index: | >80 | Index: | 657269 |
| SDCM: | ≤ 3 | EAN: | 5905963657269 |
| Power factor: | 0.62 | Category type: | bulkheads |
| Beam angle [°]: | 131 | Luminaire rated power P_{min} [W]: | 25.50 |
| Battery: | NiMh | AC voltage range [V]: | 198-264 |
| Battery capacity [mAh]: | 2100 | DC voltage range [V]: | 176-276 |
| Diffuser material: | PMMA | UGR (4H8H): | 16,1-24,1 |
| Diffuser colour: | white | Light distribution type: | lambertian |
| | | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| | | Impact resistance: | IK02 |
| | | Manual: | Download PDF |
| | | Plik LDT: | |

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 390/2023