

# DEIMOS LED PLUS 2850LM 830 IP40 I KL. DALI RCR BIAŁY 26W 400MM CORRIDOR

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	657085
Ingress protection:	IP40
Nominal power [W]:	26
Luminous flux [lm]*:	2850
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	HIPS
Diffuser material:	PMMA
Diffuser type:	OPAL

## CHARACTERISTICS

Surface mounted, round LED fitting with very high diffuser diameter, high luminous flux and even light distribution. Includes an integrated energy-saving light source LED GO!. HIPS base, powder coated white and black; light, white diffuser made using termoforming method. Simple pawl-based mounting system does not require any additional tools. The luminaire may be used to replace standard four-lamp fittings in irregular shaped rooms.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- radio motion sensor,
- corridor function,
- DALI,
- emergency module.

## APPLICATION

Surface mounted fitting intended for indoor use characterized by even light distribution and good surface lighting. Particularly suitable as a general light source in representative rooms and passageways. Thanks to exceptional lighting parameters, possible integration with the DALI system and decorative qualities, the product will surely prove its worth in large conference halls.


# DEIMOS LED PLUS 2850LM 830 IP40 I KL. DALI RCR BIAŁY 26W 400MM CORRIDOR

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Mounting dimensions [mm]:	306/329
Nominal power [W]:	26	Ingress protection:	IP40
Rated power of the luminaire [W]:	29	Mounting version:	surface
Supply voltage [V]:	220-240	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	2850	Corridor function:	yes
Luminous efficacy [lm/W]:	99	Motion sensor:	yes
Energy efficiency class:	E	DIMM DALI:	yes
Electrical protection class:	I	Accessories included:	mounting pins
Colour temperature [K]:	3000	Dimensions of single box [mm]:	445/445/123
Colour rendering index:	>80	Net weight [kg]:	1.600
SDCM:	≤ 3	Warranty [years]:	5
Max load (RCR) [W]:	400	CE certificate:	<a href="#">390/2023</a>
Beam angle [°]:	131	Index:	657085
Battery:	NiMh	EAN:	5905963657085
Battery capacity [mAh]:	2100	Category type:	bulkheads
Diffuser material:	PMMA	Luminaire rated power Omin [W]:	29.50
Diffuser type:	OPAL	UGR (4H8H):	17-25
Diffuser colour:	white	Light distribution type:	lambertian
Optics material:	PMMA	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Optics:	lens	Impact resistance:	IK02
Material of the body:	HIPS	Manual:	<a href="#">Download PDF</a>
Colour of the body:	white	Plik LDT:	<a href="#">Download</a>
Dimensions (H/W/T/S) [mm]:	ø400/100		

## LIGHT CURVES



Card creation date:10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 390/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)