

DEIMOS LED PLUS 3100LM 840 IP40 I KL. DALI BIAŁY 26W 400MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	657146
Ingress protection:	IP40
Nominal power [W]:	26
Luminous flux [lm]*:	3100
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	HIPS
Diffuser material:	PMMA
Diffuser type:	OPAL

CHARACTERISTICS

Surface mounted, round LED fitting with very high diffuser diameter, high luminous flux and even light distribution. Includes an integrated energy-saving light source LED GO!. HIPS base, powder coated white and black; light, white diffuser made using termoforming method. Simple pawl-based mounting system does not require any additional tools. The luminaire may be used to replace standard four-lamp fittings in irregular shaped rooms.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- radio motion sensor,
- corridor function,
- DALI,
- emergency module.

APPLICATION

Surface mounted fitting intended for indoor use characterized by even light distribution and good surface lighting. Particularly suitable as a general light source in representative rooms and passageways. Thanks to exceptional lighting parameters, possible integration with the DALI system and decorative qualities, the product will surely prove its worth in large conference halls.


DEIMOS LED PLUS 3100LM 840 IP40 I KL. DALI BIAŁY 26W 400MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	ø400/100
Nominal power [W]:	26	Mounting dimensions [mm]:	306/332
Rated power of the luminaire [W]:	28	Ingress protection:	IP40
Supply voltage [V]:	220-240	Mounting version:	surface
Luminous flux [lm]:	3100	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	111	DIMM DALI:	yes
Energy efficiency class:	E	Accessories included:	mounting pins
Electrical protection class:	I	Dimensions of single box [mm]:	445/445/126
Colour temperature [K]:	4000	Net weight [kg]:	1.400
Colour rendering index:	80	Warranty [years]:	5
SDCM:	≤ 3	CE certificate:	390/2023
Beam angle [°]:	131	Index:	657146
Battery:	NiMh	EAN:	5905963657146
Battery capacity [mAh]:	2100	Category type:	bulkheads
Diffuser material:	PMMA	Luminaire rated power 0min [W]:	29
Diffuser type:	OPAL	UGR (4H8H):	17-25
Diffuser colour:	white	Light distribution type:	lambertian
Optics material:	PMMA	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Optics:	lens	Impact resistance:	IK02
Material of the body:	HIPS	Manual:	Download PDF
Colour of the body:	white	Plik LDT:	Download

LIGHT CURVES



Card creation date:10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 390/2023

 **LENA**
LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl