

CORONA STREET LED EVO RM1 6250LM I KL. IP66 757 SP10KV (42W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|-------------------------------------|--------|
| Index: | 644641 |
| Ingress protection: | IP66 |
| Impact resistance: | IK08 |
| Nominal power [W]: | 42 |
| Luminous flux [lm]*: | 6300 |
| Colour temperature [K]: | 5700 |
| SDCM: | ≤ 3 |
| Colour rendering index: | >70 |
| Electrical protection class: | I |
| Energy efficiency class: | C |

CHARACTERISTICS

Road LED fitting with integrated energy-saving LED module and high luminous flux. The body and handle has been made out of die cast aluminum, powder painted in gray (RAL9006). Accessory cover made out of plastic. The fitting uses directional lens matrices made of PMMA, available versions: RM1 (Road Medium 1), RW1 (Road Wide 1). Lampshade is made out of hardened glass. IP66 ingress protection class and IK08 impact-rating features make this fitting extremely tight and shock-resistant (vandal-resistant). Integrated, step-regulated grip allows to set the fitting. Beam angle adjustment: 0° to +15° (peak to pole); -15° to 0° (side to boom). Options: First class protection, DALI and LineSwitch control, ability to program 5-step power reduction, CLO - maintaining luminous flux in time. Equipped with surge protection SP10kV as standard.

APPLICATION

This road fitting is designed to be used in open areas for lighting: highways, expressways, streets, local roads, crossroads and car-parks.


CORONA STREET LED EVO RM1 6250LM I KL. IP66 757 SP10KV (42W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|-------------|---------------------------------|---|
| Light source: | LED module | Mounting version: | on the pole |
| Nominal power [W]: | 42 | Working temperature [°C]: | from -20 to +35 |
| Rated power of the luminaire [W]: | 42 | Tilt angle adjustment [°]: | 0 to +15 (peak to pole); -15 to 0 (side to boom) |
| Supply voltage [V]: | 220-240 | Lateral surface (SCx) [m2]: | 0.020 |
| Luminous flux [lm]: | 6300 | Number on the palette [pcs]: | 18 |
| Luminous efficacy [lm/W]: | 150 | Net weight [kg]: | 4.300 |
| Energy efficiency class: | C | CE certificate: | 96/2023 |
| Electrical protection class: | I | Index: | 644641 |
| Colour temperature [K]: | 5700 | EAN: | 5905963644641 |
| Colour rendering index: | >70 | Category type: | street lighting |
| SDCM: | ≤ 3 | Category of application: | parkings and bicycle paths |
| Power factor: | 0.93 | Version: | RM1 |
| Surge protection [kV]: | 10 | Luminaire rated power Omin [W]: | 42.10 |
| Diffuser material: | glass | LED lifespan L90B10 [h]: | 100000 |
| Diffuser colour: | transparent | Light distribution type: | RM1 |
| Optics material: | PMMA | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| Optics: | matrix lens | ENEC Certificate: | BBJ/004/2019 |
| Material of the body: | aluminium | Warranty [years]: | 5 |
| Colour of the body: | grey | ETIM class: | EC000062 |
| Dimensions (H/W/T/S) [mm]: | 648/262/128 | Warranty [years]: | 5 |
| Mounting dimensions [mm]: | ∅60 | ULOR: | 0% |
| Impact resistance: | IK08 | Manual: | Download PDF |
| Ingress protection: | IP66 | | |

LIGHT CURVES



CORONA STREET LED EVO RM1 6250LM I KL. IP66 757 SP10KV (42W)

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|---------|--------------------------|
| UL00141 | mounting grip 76mm |
| 314049 | wall holder (galvanized) |
| 314056 | wall holder (grey) |



mounting grip 76mm (UL00141)



wall holder (galvanized) (314049)



wall holder (grey) (314056)

Card creation date: 08 August 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 96/2023