

CORONA STREET LED EVO RW1 11800LM DALI II KL. IP66 757 SP10KV (85W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	641473
Ingress protection:	IP66
Impact resistance:	IK08
Nominal power [W]:	85
Luminous flux [lm]*:	11800
Colour temperature [K]:	5700
SDCM:	≤ 3
Colour rendering index:	>70
Electrical protection class:	II
Energy efficiency class:	C

CHARACTERISTICS

Road LED fitting with integrated energy-saving LED module and high luminous flux. The body and handle has been made out of die cast aluminum, powder painted in gray (RAL9006). Accessory cover made out of plastic. The fitting uses directional lens matrices made of PMMA, available versions: RM1 (Road Medium 1), RW1 (Road Wide 1). Lampshade is made out of hardened glass. IP66 ingress protection class and IK08 impact-rating features make this fitting extremely tight and shock-resistant (vandal-resistant). Integrated, step-regulated grip allows to set the fitting. Beam angle adjustment: 0° to +15° (peak to pole); -15° to 0° (side to boom). Options: First class protection, DALI and LineSwitch control, ability to program 5-step power reduction, CLO - maintaining luminous flux in time. Equipped with surge protection SP10kV as standard.

APPLICATION

This road fitting is designed to be used in open areas for lighting: highways, expressways, streets, local roads, crossroads and car-parks.

CORONA STREET LED EVO RW1 11800LM DALI II KL. IP66 757 SP10KV (85W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Working temperature [°C]:	from -20 to +35
Nominal power [W]:	85	Beam angle adjustment [°]:	0 to +15 (peak to pole); -15 to 0 (side to boom)
Rated power of the luminaire [W]:	85	Lateral surface (SCx) [m2]:	0.020
Supply voltage [V]:	220-240	DIMM DALI:	yes
Frequency [Hz]:	50 - 60	Number on the palette [pcs]:	18
Luminous flux [lm]:	11800	Net weight [kg]:	4.300
Luminous efficacy [lm/W]:	139	CE certificate:	96/2023
Energy efficiency class:	C	Index:	641473
Electrical protection class:	II	EAN:	5905963641473
Colour temperature [K]:	5700	Category type:	street lighting
Colour rendering index:	>70	Category of application:	parkings and bicycle paths
SDCM:	≤ 3	Version:	RW1
Power factor:	0.98	Luminaire rated power Omin [W]:	84.40
Surge protection [kV]:	10	AC voltage range [V]:	198 - 264
Diffuser material:	glass	DC voltage range [V]:	186 - 250
Diffuser colour:	transparent	LED lifespan L90B10 [h]:	100000
Optics material:	PMMA	Light distribution type:	RW1
Optics:	matrix lens	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Material of the body:	aluminium	ENEC Certificate:	BBJ/005/2019
Colour of the body:	grey	Warranty [years]:	5
Dimensions (H/W/T/S) [mm]:	648/262/128	ETIM class:	EC000062
Mounting dimensions [mm]:	ø60	Warranty [years]:	5
Impact resistance:	IK08	ULOR:	0%
Ingress protection:	IP66	Manual:	Download PDF
Mounting version:	on the pole		

LIGHT CURVES



CORONA STREET LED EVO RW1 11800LM DALI II KL. IP66 757 SP10KV (85W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
UL00141	mounting grip 76mm
314049	wall holder (galvanized)
314056	wall holder (grey)



mounting grip 76mm (UL00141)



wall holder (galvanized) (314049)



wall holder (grey) (314056)

Card creation date: 08 August 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 96/2023