CORONA STREET LED EVO RW1 7650LM DALI I KL. IP66 757 SP10KV (53W)

DETAILED CARD

TECHNICAL PARAMETERS

Index:	x
Ingress protection:	IP44; IP66
Impact resistance:	IK08
Nominal power [W]:	30
Luminous flux [lm]*:	3850 - 13250
Colour temperature [K]:	3000; 4000; 5000; 5700
SDCM:	≤ 3; ≤ 5
Colour rendering index:	> 70; > 80; >70; >80
Electrical protection class:	I; II
Energy efficiency class:	C; D

CHARACTERISTICS

Road LED fitting with integrated energy-saving LED module and high luminous flux. The body and handle has been made out of die cast aluminum, powder painted in gray (RAL9006). Accessory cover made out of plastic. The fitting uses directional lens matrices made of PMMA, available versions: RM1 (Road Medium 1), RW1 (Road Wide 1). Lampshade is made out of hardened glass. IP66 ingress protection class and IK08 impact-rating features make this fitting extremely tight and shock-resistant (vandal-resistant). Integrated, step-regulated grip allows to set the fitting. Beam angle adjustment: 0° to +15° (peak to pole); -15° to 0° (side to boom). Options: First class protection, DALI and LineSwitch control, ability to program 5-step power reduction, CLO - maintaining luminous flux in time. Equipped with surge protection SP10kV as standard.

APPLICATION

This road fitting is designed to be used in open areas for lighting: highways, expressways, streets, local roads, crossroads and car-parks.

CORONA STREET LED EVO RW1 7650LM DALI I KL. IP66 757 SP10KV (53W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	moduł LED
Nominal power [W]:	30
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous flux [lm]:	3850 - 13250
Energy efficiency class:	C; D
Electrical protection class:	I; II
Colour temperature [K]:	3000; 4000; 5000; 5700
Colour rendering index:	> 70; > 80; >70; >80
SDCM:	≤ 3; ≤ 5
Surge protection [kV]:	10
Diffuser material:	Szyba hartowana; szkło
Diffuser colour:	transparentny
Optics material:	PMMA
Optics:	RM1; matryca soczewkowa
Material of the body:	Aluminium malowane proszkowo; aluminium
Colour of the body:	czarny RAL9005; szary; szary RAL 9006
Dimensions (H/W/T/S) [mm]:	648/262/128
Mounting dimensions [mm]:	ø60; ø76
Impact resistance:	IK08
Ingress protection:	IP44; IP66
Mounting version:	Szczytowy, na słupie / Boczny, na wysięgniku; na słupie
Working temperature [°C]:	od -20 do +35; od -20 do +35; od -30 do +45
Beam angle adjustment [°]:	od 0 do +15 (szczytowy, na słupie); -15 do 0 (boczny, na wysięgniku)

Lateral surface (SCx) [m2]:	0.020
DIMM DALI:	yes
Number on the palette [pcs]:	18
Net weight [kg]:	4.300
CE certificate:	130/2018; 96/2023
Index:	x
EAN:	x
Category type:	street lighting
Category of application:	parkings and bicycle paths
Version:	RM1; RW1
AC voltage range [V]:	198 - 264
DC voltage range [V]:	186 - 250
LED lifespan L90B10 [h]:	100000
Light distribution type:	RM1; RW1
Photobiological safety:	grupa ryzyka 1 (niskie ryzyko)
ENEC Certificate:	BBJ/004/2019; BBJ/005/2019
Warranty [years]:	5
ETIM class:	EC000062
Warranty [years]:	5
ULOR:	0%
Wire type:	H07RN-F 3x1,5
Cable length [m]:	0.70
Manual:	Download PDF

LIGHT CURVES



CORONA STREET LED EVO RW1 7650LM DALI I KL. IP66 757 SP10KV (53W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
UL00141	mounting grip 76mm
314049	wall holder (galvanized)
314056	wall holder (grey)

mounting grip 76mm (UL00141)



wall holder (galvanized) (314049)

wall holder (grey) (314056)

Card creation date: 08 August 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 96/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl