## **ROUND LED HV 210MM 570LM 830 BIAŁY KRATKA (5W)**

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

Index:	948008
Ingress protection:	IP44
Impact resistance:	IK06
Nominal power [W]:	5
Luminous flux [lm]*:	570
Colour temperature [K]:	3000
SDCM:	≤ 4
Energy efficiency class:	F
Material of the body:	PP
Diffuser material:	glass

#### **CHARACTERISTICS**

Surface mounted, round LED luminaire with an integrated, energy-saving LED GO! panel with high luminous efficacy and ingress protection of IP44. The base is available in white, black and gray. It was made of polypropylene and the diffuser is made of prismatic glass. The luminaire is available with a presence detector (PIR).

## **APPLICATION**

Round, surface mounted luminaire for mounting on ceilings and walls; intended for indoor use (rooms with high humidity, passageways and staircases, sewers and basements) as well as outdoor use (industrial facade lighting, parking lots).



# ROUND LED HV 210MM 570LM 830 BIAŁY KRATKA (5W)

**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

Light source:	LED module
Nominal power [W]:	5
Rated power of the luminaire [W]:	6.10
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	570
Luminous efficacy [lm/W]:	93
Energy efficiency class:	F
Electrical protection class:	1
Colour temperature [K]:	3000
Colour rendering index:	>80
SDCM:	≤ 4
Power factor:	0.99
Diffuser material:	glass
Diffuser type:	PRM
Material of the body:	PP

Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	ø210/105
Impact resistance:	IK06
Ingress protection:	IP44
Mounting version:	surface
Working temperature [°C]:	from 0 to +25
Net weight [kg]:	0.700
CE certificate:	<u>16/2018</u>
Index:	948008
EAN:	5905963948008
Category type:	bulkheads
Category of application:	parkings and bicycle paths
Version:	grid
Luminaire rated power 0min [W]:	6.10
Warranty [years]:	5
Manual:	Download PDF

Card creation date: 12 May 2020



