ROUND LED HV 220MM 590LM 830 BIAŁY PIERŚCIEŃ (5W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:	948244
Ingress protection:	IP44
Impact resistance:	IK06
Nominal power [W]:	5
Luminous flux [lm]*:	590
Colour temperature [K]:	3000
SDCM:	≤ 4
Energy efficiency class:	Е
Material of the body:	PP
Diffuser material:	glass

CHARACTERISTICS

Surface mounted, round LED luminaire with an integrated, energy-saving LED GO! panel with high luminous efficacy and ingress protection of IP44. The base is available in white, black and gray. It was made of polypropylene and the diffuser is made of prismatic glass. The luminaire is available with a presence detector (PIR).

APPLICATION

Round, surface mounted luminaire for mounting on ceilings and walls; intended for indoor use (rooms with high humidity, passageways and staircases, sewers and basements) as well as outdoor use (industrial facade lighting, parking lots).



ROUND LED HV 220MM 590LM 830 BIAŁY PIERŚCIEŃ (5W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	5
Rated power of the luminaire [W]:	6.10
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [Im]:	590
Luminous efficacy [lm/W]:	97
Energy efficiency class:	Е
Electrical protection class:	1
Colour temperature [K]:	3000
Colour rendering index:	>80
SDCM:	≤ 4
Power factor:	0.99
Diffuser material:	glass
Diffuser type:	PRM
Material of the body:	PP

Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	ø220/90
Impact resistance:	IK06
Ingress protection:	IP44
Mounting version:	surface
Working temperature [°C]:	from 0 to +25
Net weight [kg]:	0.750
CE certificate:	<u>16/2018</u>
Index:	948244
EAN:	5905963948244
Category type:	bulkheads
Category of application:	parkings and bicycle paths
Version:	ring
Luminaire rated power 0min [W]:	6.10
Warranty [years]:	5
Manual:	Download PDF

Card creation date: 12 May 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

