

PILLAR 2 LED 1420LM 830 IP65 I CL. 25° (16W) RAL 7037

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------------|------------------|
| Index: | x |
| Ingress protection: | IP65 |
| Impact resistance: | IK07 |
| Rated power of the luminaire [W]*: | 10 |
| Luminous flux [lm]*: | 950 - 1595 |
| Colour temperature [K]: | 3000; 4000; 5700 |
| Energy efficiency class: | E; F |
| Material of the body: | aluminium |
| Diffuser material: | szkło hart. |
| Diffuser type: | transparentny |

CHARACTERISTICS

This energy-saving, outdoor accent LED fitting ensures economical and long-term operation without the need to replace light sources. It has high ingress protection rating of IP65—from dust ingress and water jets from any direction. The ingress protection is ensured by its design—aluminium body and tempered glass additionally protected with a seal. The fitting is available in two light distribution options.

APPLICATION

The fitting for wall mounting (directly to the surface by means of wall plugs) is designed especially for accent outdoor lighting of facades of: hotels, offices, apartment buildings but also private houses, passageways and entrance areas.

PILLAR 2 LED 1420LM 830 IP65 I CL. 25° (16W) RAL 7037

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|------------------------|----------------------------|---|
| Light source: | moduł LED | Colour of the body: | RAL7037 |
| Rated power of the luminaire [W]: | 10 | Dimensions (H/W/T/S) [mm]: | 130/76/129; 175/76/136; 175/76/136,5 |
| Supply voltage [V]: | 220-240 | Mounting dimensions [mm]: | fi 80; fi 80/23; 80 |
| Frequency [Hz]: | 50-60 | Impact resistance: | IK07 |
| Luminous flux [lm]: | 950 - 1595 | Ingress protection: | IP65 |
| Energy efficiency class: | E; F | Net weight [kg]: | 0.300; 0.500 |
| Electrical protection class: | I | Warranty [years]: | 2 |
| Colour temperature [K]: | 3000; 4000; 5700 | Index: | x |
| Beam angle [°]: | 15; 24; 25; 38; 50; 60 | EAN: | x |
| Diffuser material: | szkło hart. | Category type: | accent lighting |
| Diffuser type: | transparentny | Version: | góra i dół; góra lub dół |
| Optics material: | PC | AC voltage range [V]: | 220 - 240 |
| Optics: | Reflektor | Photobiological safety: | grupa ryzyka 1 (niskie ryzyko) |
| Material of the body: | aluminium | Manual: | Pobierz PDF |

Card creation date:12 January 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 88/2019



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl