PILLAR 2 LED 1465LM 830 IP65 I CL. 38° (16W) RAL 7037

DETAILED CARD



TECHNICAL PARAMETERS

Index:

Ingress protection: IP65

Impact resistance: IK07

Rated power of the luminaire [W]*: 10

Luminous flux [lm]*: 950 - 1595

Colour temperature [K]: 3000; 4000; 5700

Energy efficiency class: E; F

Material of the body: aluminium

Diffuser material: szkło hart.

Diffuser type: transparentny

CHARACTERISTICS

This energy-saving, outdoor accent LED fitting ensures economical and long-term operation without the need to replace light sources. It has high ingress protection rating of IP65—from dust ingress and water jets from any direction. The ingress protection is ensured by its design—aluminium body and tempered glass additionally protected with a seal. The fitting is available in two light distribution options.

APPLICATION

The fitting for wall mounting (directly to the surface by means of wall plugs) is designed especially for accent outdoor lighting of facades of: hotels, offices, apartment buildings but also private houses, passageways and entrance areas.



PILLAR 2 LED 1465LM 830 IP65 I CL. 38° (16W) RAL 7037

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	moduł LED
Rated power of the luminaire [W]:	10
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous flux [lm]:	950 - 1595
Energy efficiency class:	E; F
Electrical protection class:	1
Colour temperature [K]:	3000; 4000; 5700
Beam angle [°]:	15; 24; 25; 38; 50; 60
Diffuser material:	szkło hart.
Diffuser type:	transparentny
Optics material:	PC
Optics:	Reflektor
Material of the body:	aluminium

Colour of the body:	RAL7037
Dimensions (H/W/T/S) [mm]:	130/76/129; 175/76/136; 175/76/136,5
Mounting dimensions [mm]:	fi 80; fi 80/23; 80
Impact resistance:	IK07
Ingress protection:	IP65
Net weight [kg]:	0.300; 0.500
Warranty [years]:	2
Index:	Х
EAN:	х
Category type:	accent lighting
Version:	góra i dół; góra lub dół
AC voltage range [V]:	220 - 240
Photobiological safety:	grupa ryzyka 1 (niskie ryzyko)
Manual:	Pobierz PDF

Card creation date: 12 January 2021



