

PILLAR 2 LED 1450LM 840 IP65 I CL. 60° (16W) RAL 7037

DETAILED CARD



TECHNICAL PARAMETERS

Index:	958793
Ingress protection:	IP65
Impact resistance:	IK07
Rated power of the luminaire [W]*:	16
Luminous flux [lm]*:	1450
Colour temperature [K]:	4000
Energy efficiency class:	F
Material of the body:	aluminium
Diffuser material:	tempered glass
Diffuser type:	transparent

CHARACTERISTICS

This energy-saving, outdoor accent LED fitting ensures economical and long-term operation without the need to replace light sources. It has high ingress protection rating of IP65—from dust ingress and water jets from any direction. The ingress protection is ensured by its design—aluminium body and tempered glass additionally protected with a seal. The fitting is available in two light distribution options.

APPLICATION

The fitting for wall mounting (directly to the surface by means of wall plugs) is designed especially for accent outdoor lighting of facades of: hotels, offices, apartment buildings but also private houses, passageways and entrance areas.

PILLAR 2 LED 1450LM 840 IP65 I CL. 60° (16W) RAL 7037

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	175/76/136
Rated power of the luminaire [W]:	16	Mounting dimensions [mm]:	80
Supply voltage [V]:	220-240	Impact resistance:	IK07
Frequency [Hz]:	50 - 60	Ingress protection:	IP65
Luminous flux [lm]:	1450	Net weight [kg]:	0.500
Energy efficiency class:	F	Warranty [years]:	2
Electrical protection class:	I	Index:	958793
Colour temperature [K]:	4000	EAN:	5905963958793
Beam angle [°]:	60	Category type:	accent lighting
Diffuser material:	tempered glass	Version:	up and down
Diffuser type:	transparent	AC voltage range [V]:	220 - 240
Optics material:	PC	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Optics:	Reflektor	Luminous efficacy [lm/W]:	91
Material of the body:	aluminium	Manual:	Download PDF
Colour of the body:	RAL7037		

Card creation date:12 January 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 88/2019



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl