PILLAR 3 LED 1005LM 830 IP65 I CL. 15° (10W) RAL 7037

DETAILED CARD



TECHNICAL PARAMETERS

Index:	958571	
Ingress protection:	IP65	
Impact resistance:	IK07	
Rated power of the luminaire [W]*:	10	
Luminous flux [lm]*:	1005	
Colour temperature [K]:	3000	
Energy efficiency class:	E	
Material of the body:	aluminium	
Diffuser material:	tempered glass	
Diffuser type:	transparent	

CHARACTERISTICS

This energy-saving, outdoor accent LED fitting ensures economical and long-term operation without the need to replace light sources. It has high ingress protection rating of IP65—from dust ingress and water jets from any direction. The ingress protection is ensured by its design—aluminium body and tempered glass additionally protected with a seal. The fitting is available in two light distribution options.

APPLICATION

The fitting for wall mounting (directly to the surface by means of wall plugs) is designed especially for accent outdoor lighting of facades of: hotels, offices, apartment buildings but also private houses, passageways and entrance areas.



PILLAR 3 LED 1005LM 830 IP65 I CL. 15° (10W) RAL 7037

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Dimensions (H/W/T/S) [mm]:	130/76/129
-			
Rated power of the luminaire [W]:	10	Mounting dimensions [mm]:	fi 80/23
Supply voltage [V]:	220-240	Impact resistance:	IK07
Frequency [Hz]:	50 - 60	Ingress protection:	IP65
Luminous flux [lm]:	1005	Net weight [kg]:	0.300
Energy efficiency class:	E	Warranty [years]:	2
Electrical protection class:	1	Index:	958571
Colour temperature [K]:	3000	EAN:	5905963958571
Beam angle [°]:	15	Category type:	accent lighting
Diffuser material:	tempered glass	Version:	up or down
Diffuser type:	transparent	AC voltage range [V]:	220 - 240
Optics material:	PC	N	Risk Group 1 (no photobiological hazard under normal behavioral
Optics:	Reflektor	Photobiological safety:	limitation)
Material of the body:	aluminium	Luminous efficacy [lm/W]:	101
Colour of the body:	RAL7037	Manual:	Download PDF

Card creation date: 12 January 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

Certificate CE - Nr: 88/2019

This product is a subject to electric and electronic waste equipment regulations (WEEE).

