PILLAR 3 LED 1000LM 840 IP65 I CL. 38° (10W) RAL 7037

DETAILED CARD



TECHNICAL PARAMETERS

Index:	958649
Ingress protection:	IP65
Impact resistance:	IK07
Rated power of the luminaire [W]*:	10
Luminous flux [lm]*:	1000
Colour temperature [K]:	4000
Energy efficiency class:	E
Material of the body:	aluminium
Diffuser material:	tempered glass
Diffuser type:	transparent

CHARACTERISTICS

This energy-saving, outdoor accent LED fitting ensures economical and long-term operation without the need to replace light sources. It has high ingress protection rating of IP65—from dust ingress and water jets from any direction. The ingress protection is ensured by its design—aluminium body and tempered glass additionally protected with a seal. The fitting is available in two light distribution options.

APPLICATION

The fitting for wall mounting (directly to the surface by means of wall plugs) is designed especially for accent outdoor lighting of facades of: hotels, offices, apartment buildings but also private houses, passageways and entrance areas.

PILLAR 3 LED 1000LM 840 IP65 I CL. 38° (10W) RAL 7037

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module
Rated power of the luminaire [W]:	10
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	1000
Energy efficiency class:	E
Electrical protection class:	I
Colour temperature [K]:	4000
Beam angle [°]:	38
Diffuser material:	tempered glass
Diffuser type:	transparent
Optics material:	PC
Optics:	Reflektor
Material of the body:	aluminium
Colour of the body:	RAL7037

Dimensions (H/W/T/S) [mm]:	130/76/129
Mounting dimensions [mm]:	fi 80/23
Impact resistance:	IK07
Ingress protection:	IP65
Net weight [kg]:	0.300
Warranty [years]:	2
Index:	958649
EAN:	5905963958649
Category type:	accent lighting
Version:	up or down
AC voltage range [V]:	220 - 240
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Luminous efficacy [lm/W]:	100
Manual:	Download PDF

Card creation date: 12 January 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 88/2019

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl