

# PILLAR 3 LED 970LM 840 IP65 I CL. 60° (10W) RAL 7037

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	958670
<b>Ingress protection:</b>	IP65
<b>Impact resistance:</b>	IK07
<b>Rated power of the luminaire [W]*:</b>	10
<b>Luminous flux [lm]*:</b>	970
<b>Colour temperature [K]:</b>	4000
<b>Energy efficiency class:</b>	E
<b>Material of the body:</b>	aluminium
<b>Diffuser material:</b>	tempered glass
<b>Diffuser type:</b>	transparent

## CHARACTERISTICS

This energy-saving, outdoor accent LED fitting ensures economical and long-term operation without the need to replace light sources. It has high ingress protection rating of IP65—from dust ingress and water jets from any direction. The ingress protection is ensured by its design—aluminium body and tempered glass additionally protected with a seal. The fitting is available in two light distribution options.

## APPLICATION

The fitting for wall mounting (directly to the surface by means of wall plugs) is designed especially for accent outdoor lighting of facades of: hotels, offices, apartment buildings but also private houses, passageways and entrance areas.

# PILLAR 3 LED 970LM 840 IP65 I CL. 60° (10W) RAL 7037

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Light source:</b>	LED module	<b>Dimensions (H/W/T/S) [mm]:</b>	130/76/129
<b>Rated power of the luminaire [W]:</b>	10	<b>Mounting dimensions [mm]:</b>	fi 80/23
<b>Supply voltage [V]:</b>	220-240	<b>Impact resistance:</b>	IK07
<b>Frequency [Hz]:</b>	50 - 60	<b>Ingress protection:</b>	IP65
<b>Luminous flux [lm]:</b>	970	<b>Net weight [kg]:</b>	0.300
<b>Energy efficiency class:</b>	E	<b>Warranty [years]:</b>	2
<b>Electrical protection class:</b>	I	<b>Index:</b>	958670
<b>Colour temperature [K]:</b>	4000	<b>EAN:</b>	5905963958670
<b>Beam angle [°]:</b>	60	<b>Category type:</b>	accent lighting
<b>Diffuser material:</b>	tempered glass	<b>Version:</b>	up or down
<b>Diffuser type:</b>	transparent	<b>AC voltage range [V]:</b>	220 - 240
<b>Optics material:</b>	PC	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Optics:</b>	Reflektor	<b>Luminous efficacy [lm/W]:</b>	97
<b>Material of the body:</b>	aluminium	<b>Manual:</b>	Download PDF
<b>Colour of the body:</b>	RAL7037		

Card creation date: 12 January 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 88/2019